

Mine Safety Appliances Company · John T. Ryan Memorial Lab 1100 Cranberry Woods Drive, Cranberry Township, PA 16066

MSA Engineering Self Certification of Standard Compliance IAC-23-025-Z04-001

Statement of Compliance: This Cable Anchorage Connector Extension or Cable Anchorage Sling meets the requirements of ANSI/ASSE Z359.1-2007, Safety Requirements for Personal Fall Arrest Systems, Subsystems and Components.

Tested part number(s) or IAC No.:	"Sold as" part number(s)/Market:	
IAC 025	SEE ATTACHED IAC-23-025 COMPLIANCE	
	REPORT REV 1	

Test Facility & Document #: CSA GROUP - IAC025LD

PERFORMANCE DETAILS

	(May format as needed)		
List standard and referenced sections as applicable	Results	Pass / Fail	
SEE ATTACHED COMPLIANCE REPORT			

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222 (for industrial products) or Safety Works Customer Service at 1-800-969-7562 (for retail products). When requesting information, please reference "sold as" part number(s).

Quality Assurance: June 15000

TAMES WONDERLING

Date: JUNE 17, 2013

File name: IAC 025_SCP-Z04.docx

SCP-Z04 - SelfCertForm



ANSI Z359.7 3rd Party Testing Compliance Report Revision 1

IAC 025 - CABLE ANCHORAGE CONNECTOR EXTENSION AND ANCHORAGE CABLE SLING

"Sold As" Part numbers	SFP3267501, SFP6237502, SFP3267503, SFP3267504, SFP3267505, SFP3267506, SFP3267507, SFP3267508, SFP3267510, SFP3267512, SFP3267514, SFP3267518, 505233, 10001609, 10002182, 10008492, 10044724 10059264, 10073847, 10080173, 10082683, 10082774, 10084866, 10087003, 10095264, 10103905		
ANSI Z359.1-2007 Requirement	Results	Pass/Fail	
3.2.5 Anchorage Connector Component	MSA Cable Anchorage Connector Extensions and Anchorage Cable Slings meet all design and testing requirements put forth by ANSI Z359.1	Pass	
3.2.5.1 Anchorage connectors shall meet the strength requirements of the anchorages to which they are coupled as set forth in 7.2.3. Satisfactory completion of the pullification testing specified in 4.3.6 shall constitute compliance with this requirement. When tested in accordance with 4.3.6, anchorage connectors shall be capable of withstanding (without breaking) a 5,000-pound 22.2kN) load multiplied by the maximum number of beersonal fall arrest systems that may be attached to the anchorage connector. Connector elements integral to or part of the anchorage connector shall be capable of withstanding a 3,600-pound (16kN) load without cracking, breaking, or bermanent deformation visible to the unaided eye.	MSA Cable Anchorage Connector Extensions and Anchorage Cable Slings meet qualification testing requirements as specified in 4.3.6. 3,600-pound (16kN) static tensile test for without cracking, breaking, or permanent deformation visible to the unaided eye. 5,000-pound (22.2kN) static tensile test, maintained for one minute, without breaking.	Pass	
1.2.5.2 An anchorage connector shall be attached to no nore than one PFAS unless certified for such purpose. When an anchorage connector is part of more than one PFAS, the anchorage connector strengths set forth in 1.2.5.1 shall be multiplied by the number of PFAS of which it is a part.	MSA Cable Anchorage Connector Extensions and Anchorage Cable Slings are designed to be part of one PFAS.	Pass	
3.2.5.3 The stability and compatibility of couplings between anchorage connectors and anchorages shall be considered in anchorage connector design.	MSA Cable Anchorage Connector Extensions and Anchorage Cable Slings are designed to be a stable connection to the anchorage appropriate for its use, as outlined in the user instructions	Pass	
3.2.5.4 The exposure of anchorage connectors to sharp adges, abrasive surfaces, and physical hazards such as hermal, electrical, and chemical sources shall be considered in anchorage connector design.	MSA Cable Anchorage Connector Extensions and Anchorage Cable Slings are designed with the environmental and physical hazards of recommended use taken into account.	Pass	