



The Safety Company

1000 Cranberry Woods Drive,
Cranberry Township, PA 16066

MSA Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014

IAC-23-051 - Z04 Rev 1

Statement of Conformity: MSA declares that the
Workman Mini PFL
is in conformity with the requirements of

Insert the standard Name and Number that the item was tested to and in compliance with.

Table with 2 columns: Product Code, Model / Part Numbers Covered. Row 1: IAC-23-051, 10157841, 10157842, 10157834, 10157835, 10157836, 10157837, 10157838, 10157841, 10157842, 10157843, 10157844, 10157845, 10157858, 10157859, 10157860, 10157861, 10157862, 10186205

ANSI/ISEA 125-2014 conformity assessment method: [] Level 1 [X] Level 2

For Level 2, information about ISO 17025-accredited facility in which the product was tested:

- [X] The test facility is an independent 3rd Party
[] The test facility is owned or partially owned by an entity within supplier's corporate structure, or within the manufacturing stream for this product, including subcontractors

Table with 3 columns: Report, Test Facility Used, Test Facility Document #. Row 1: 1, Intertek, G101783981CRT-001. Row 2: 2, Intertek, G101783981CRT-002

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222. When requesting information, please reference model number(s).

Quality Assurance: David Backfisch Date: 10/31/17 10/31/2017

Performance Details

Revision 1

Report	Standard and Product Requirements	Results	Pass / Fail
1	Corrosion Section 3.1 5 (7 4)	operates as intended / no visual corrosion	Pass
1	Retraction Tension Section 3 1 6 (4 2 6)	tension between 1 25 - 25lbs	Pass
1	Dynamic Performance Section 3 1 9 (4 2 1)	Max arrest force <1800 lbf, Avg arrest force <1350 lbf, arrest distance < 24"	Pass
1	Dynamic Performance (Heat) Section 3 1.9 (4 2 8 1)	Max arest force < 1800 lbf Avg arrest force < 1350 lbf arrest distance < 24"	Pass
1	Dynamic Performance (Cold) Section 3 1 9 (4 2 8 2)	Max arest force < 1800 lbf Avg arrest force < 1350 lbf arrest distance < 24"	Pass
1	Dynamic Performance (Wet) Section 3 1 9 (4 2 8 3)	Max arest force < 1800 lbf Avg arrest force < 1350 lbf arrest distance < 24"	Pass
1	Static Strength Section 3 1 7 (4 2 5)	>3000 lbf	Pass
2	Corrosion Section 3 1 5 (7 4)	operates as intended / no visual corrosion	Pass
2	Retraction Tension Section 3 1 6 (4 2 6)	tension between 1 25 - 25lbs	Pass
2	Dynamic Strength Section 3 1 8 (4 2 3)	unit shall lock and remain locked Test weight shall not touch the ground Line constituent shall retain 1000 lb tensile strength	Pass
2	Static Strength Section 3 1 7 (4 2 5)	>3000 lbf	Pass