

Workman® Rescuer



MSA's Workman Rescuer provides fast, easy and intuitive fall protection with integral bi-directional retrieval capability. Not only does the Workman Rescuer arrest the fall, its retrieval capability allows the fallen worker to ascend or descend to a safe location. This durable, economical addition to the Workman Series of products offers fast installation and setup, ideal for applications where time and ease of use are a priority. The Workman Rescuer is also a stand-alone retractable device, as the carrying handle may be used as an anchorage attachment.

*Because every life has a **purpose...***

Workman Rescuer: Ease of Use, Many Applications

Exclusive integral bracket uses existing tripod pin, leaving fewer components to attach or become damaged or misplaced. Fall protection/retrieval mode knob simply pulls and rotates to activate. Use this device as a component of a confined space system for one application and as a standard self-retracting lanyard for another.

- Experienced and novice users will learn setup and operation quickly and effectively
- Comparable size and weight to competitive products
- Great for OGP turnarounds, construction, utilities, and other confined space applications
- QR code on product label offers instant access to setup video and additional information

Features & Benefits

The Workman Rescuer offers these standard features:

- User capacity up to 400 lbs. for personnel
- Stainless steel 3/16" wire rope
- Integral mounting bracket
- Color-coded switch for retrieval mechanism activation
- Ergonomic, stainless steel carrying handle can also be used as anchorage connection point
- Built-in shock absorber
- Robust aluminum housing with thermoplastic bumpers
- Self-locking swivel snaphook with load indicator
- Stow-able, foldable crank handle
- RFID-enabled
- Meets OSHA regulations, ANSI Z359.14 and CSA Z259.2.2

Specifications

- **Net weight**
16.3kg (includes bracket)
- **Crank handle material**
Carbon steel with zinc plating
- **Housing material**
Cast aluminum
- **Lifting and lowering gear ratio**
Gear ratio: 5:1
- **Maximum free fall distance**
2 ft. (0.6m)
- **Maximum deceleration distance**
54" (1.4m)
- **Maximum arresting force**
1800 lbs. (8Kn)

Ordering Information

P/N	Description
10158178	Workman Rescuer, stainless steel cable, 50 ft. (15m), ANSI
10158180	Workman Rescuer, stainless steel cable, 50 ft. (15m), CSA
10159755	Workman Rescuer, synthetic rope, 50 ft. (15m), ANSI



Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 2300-161-MC/ Mar 2016

© MSA 2016 Printed in U.S.A.
Subject to changes without notice

MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAsafety.com
U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

Pacific Asia Region
MSA Singapore
MSA S.E Asia Pte Ltd
35 Marsiling Industrial Estate Road 3,
#04-01, Singapore 739257
Phone: +65 6350 4500
Fax: +65 6350 4505

MSA Australia
Phone: 1300 728 672 / +61 02 9688 0333
Fax: +61 2 9896 1835

MSA Indonesia
Phone: +62 21 6409 000
Fax: +62 21 641 2831

MSA Malaysia
Phone: +603 8724 8208/9208
Fax: +603 8724 2208

MSA New Zealand
Customer Service
Phone: 0800 441 335

MSA Philippines
Phone: +63 9209 742 191

MSA Thailand
Phone: +66 2617 8211
Fax: +66 2617 8214

For sales enquiry, contact us [here](http://www.MSAsafety.com).

www.MSAsafety.com