

Workman<sup>®</sup> Winch



*The Workman Winch is rugged, versatile and economical for lifting, lowering and positioning of personnel and materials within confined space applications. Designed for maximum 400-lb workload for personnel and 620-lb for materials, the Workman Winch is built with tough thermoplastic housing to ensure high performance within the harshest environments. Winch offers integral, ergonomic carry grip and unique, foldable handle for simple storage. Patent-pending bracket design allows for easy, rapid assembly.*

*Because every life has a **purpose...***

## Features & Benefits

### All Workman Winches have several standard features:

- Rated working load 400 lbs (181 kg) for personnel and 620 lbs (282 kg) for materials
- An open drum wound with 3/16 in (5 mm) cable
- Built-in shock absorber
- Clutched drive to prevent winch overload and reduce the possibility of injury to a person if caught on a structural member during lifting
- Double-braking system
- Robust plastic housing and mounting bracket
- Self-locking swivel snaphook
- Manual foldable crank handle
- Level wind mechanism for a tangle-free cable drum
- RFID-enabled

## Features & Benefits

<b>Maximum working load</b>	Personnel: 400 lb (181 kg) Materials: 620 lb (282 kg)
<b>Line diameter</b>	Cable: 3/16 in (5 mm)
<b>Minimum line strength</b>	Cable: 3300 lb (14.7 KN)
<b>Net weight with 20 m of line</b>	Cable: 28.2 lb (12.8 kg)
<b>Swivel snaphook gate opening</b>	0.83 in (21 mm)
<b>Crank force to lift 400 lbs (181 kg)</b>	30 lb (133 N)
<b>Cranking diameter</b>	22 in (56 cm)
<b>Avg. lifting speed (400 lbs [181 kg] load)</b>	13.13 ft/min (4 m/min)

## Ordering Information



P/N	Description
10147301	Workman Winch, stainless steel cable, 65 ft. (20 m)
10153757	Workman Winch, galvanized cable, 65-ft (20m)

**Note:** This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ISO 2301-125-MC / October 2013

© MSA 2013 Printed in U.S.A.  
Subject to changes without notice

**MSA – The Safety Company**  
1000 Cranberry Woods Drive  
Cranberry Township, PA 16066 USA  
Phone 724-776-8600  
[www.MSAafety.com](http://www.MSAafety.com)

**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398

**Pacific Asia Region**  
**MSA Singapore**  
MSA S.E Asia Pte Ltd  
35 Marsiling Industrial Estate Road 3,  
#04-01, Singapore 739257  
Phone: +65 6350 4500  
Fax: +65 6350 4505

**MSA Australia**  
Phone: 1300 728 672 / +61 02 9688 0333  
Fax: +61 2 9896 1835

**MSA Indonesia**  
Phone: +62 21 6409 000  
Fax: +62 21 641 2831

**MSA Malaysia**  
Phone: +603 8724 8208/9208  
Fax: +603 8724 2208

**MSA New Zealand**  
Customer Service  
Phone: 0800 441 335

**MSA Philippines**  
Phone: +63 9209 742 191

**MSA Thailand**  
Phone: +66 2617 8211  
Fax: +66 2617 8214

For sales enquiry, contact us [here](http://www.MSAafety.com).

[www.MSAafety.com](http://www.MSAafety.com)