

### Key Helmet Features



This is the standard by which all others are judged. The V-Gard™ has been awarded an Australian Design Mark in recognition of Industrial Protective Headwear. An extended peak provides greater visibility and extra protection from sun and rain.

The peak underside of V-Gard™ is lined with MSA's patented Glaregard textured surface, a feature that significantly reduces glare, helping to reduce eye strain caused by reflected light. It also provides superior comfort and excellent impact protection.

- Extended peak for greater visibility and extra protection from sun and rain.
- Glaregard® textured underside of peak.
- Earmuff and visor attachment slots.
- Custom printing & decaling available.
- Certified to AS/NZS 1801 - Type 1.
- Replaceable sweatband available
- 7 colours available



### Suspensions features

- Two patented size adjustment systems: Staz-On with slide and Fas-Trac II with larger wheel ratchet for quick adjustment when wearing gloves.
- Made of woven polyester.
- Provide high comfort and long term, consistent shock absorption Performance.
- Preferred wearing height can be easily adjusted by pushing top crown strap.
- Ensures a consistent performance level even under the influence of moisture.
- Highly comfortable even at extremes of temperatures.
- Sophisticated 4 point attachment ensure good positioning, stability and better air circulation due to limited contact areas with the head.
- Ideal positioning of the harness through height and length adjustment, perfect for use with full-face respiratory masks.
- Replaceable sweatband with different material options are available.



## Technical Specifications

Material	
Shell	Acrylonitrile Butadiene Styrene, UV Stabilised
Sweatband	Terry Towelling, Lug style Brushed Nylon – Universal – Velcro fit (optional)
Headband & Clips	LDPE (Low density polyethylene)
Webbing	Textile (Polyester)
Approvals	
Standard	Certified to AS/NZS 1801 – Type 1.
Lifetime Guidelines	
Service Life	<p>The V-Gard Helmet are designed with high-quality, wear-resistant materials but it will not last forever. The helmet's protective properties will be degraded by exposure to many common work environments, such as temperature extremes, chemical exposure, sunlight, and normal daily wear and tear.</p> <p>MSA recommends the following replacement schedule:</p> <ul style="list-style-type: none"> <li>• <b>Suspension -Replace every 2 years</b></li> <li>• <b>shell -Replace every 3 years</b></li> </ul> <p><b>NOTE:</b> These are MAXIMUM useful service life guidelines. Wear or damage noticed during a regular inspection may determine an earlier replacement of the entire helmet. ALWAYS replace the helmet after it has withstood an impact or penetration.</p> <p>A helmet's service life starts when it is placed in service. This date should be recorded inside the helmet shell, on the label provided. Please note that the date code on the brim of your MSA V-Gard is the date of manufacture, not the starting date for useful service.</p>
General	
Shell Weight	330g
Suspensions Weight	100 g Fas-Trac 60g Staz-on
Packaging	
Individual	1 pc in polybag printed with instructions, suspension fitted.
Box	20 pieces (Staz-on) 16 pieces (Fas-Trac)
Pallet	12 boxes, 240 helmets (Staz-on) 16 boxes, 192 helmets?(Fas-Trac)

## Ordering Information

Suspension Type	V-Gard	
	Staz-on	Fas-Trac
	4 Point	4 Point
White	226000WH	226016WH
Yellow	226000YE	226016YE
Green	226000GN	226016GN
Orange	226000OR	226016OR
Red	226000RE	226016RE
Blue	226000BU	226016BU
Fluoro Lime (Yellow)	226000FL	226016FL

## Accessories

Part Number	Description
220553	Chin Strap Elastic
224047	Sweatband Brushed Nylon - Universal - Velcro Fit
765550	Sweatband, Terry Towelling, Lug Style
229068	Neck Flap Proban Yellow
229620	Repl. 4 Pt Suspension. V-Gard™ Cap
229053	4 Pt Fas-Trac Suspension



Chin Strap



Sweatband Brushed Nylon



Neck Flap Proban Yellow



Sweatband, Terry Towelling

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



Subject to changes without notice

**MSA – The Safety Company**  
 1000 Cranberry Woods Drive  
 Cranberry Township, PA 16066 USA  
 Phone 724-776-8600  
[www.MSAsafety.com](http://www.MSAsafety.com)  
**U.S. Customer Service Center**  
 Phone 1-800-MSA-2222  
 Fax 1-800-967-0398

**Pacific Asia Region**  
**MSA Singapore**  
 MSA S.E Asia Pte Ltd  
 35 Marsiling Industrial Estate Road 3,  
 #04-01, Singapore 739257  
 Phone: +65 6350 4500  
 Fax: +65 6350 4505

**MSA Australia**  
 Phone: 1300 728 672 / +61 02 9688 0333  
 Fax: +61 2 9896 1835

**MSA Indonesia**  
 Phone: +62 21 6409 000  
 Fax: +62 21 641 2831

**MSA Malaysia**  
 Phone: +603 8724 8208/9208  
 Fax: +603 8724 2208

**MSA New Zealand**  
 Customer Service  
 Phone: 0800 441 335

**MSA Philippines**  
 Phone: +63 9209 742 191

**MSA Thailand**  
 Phone: +66 2617 8211  
 Fax: +66 2617 8214

For sales enquiry, contact us [here](http://www.MSAsafety.com).