

The manufacturer may use the mark:



Revision 2.2 June 15, 2016 Surveillance Audit Due May 1, 2019



ANSI Accredited Program PRODUCT CERTIFICATION #1004

Certificate / Certificat Zertifikat / 合格証

MSA 1202040 C001

exida hereby confirms that the:

Ultima XA, Ultima XE, and Ultima XIR Gas Monitors

MSA-The Safety Company Cranberry Township, PA USA

Has been assessed per the relevant requirements of:

IEC 61508 : 2010 Parts 1-7 and meets requirements providing a level of integrity to:

Systematic Capability: SC 2 (SIL 2 Capable) Random Capability: Type B Element

Oxygen, Catalytic Combustible, IR Gas Applications: Random Integrity: SIL 2 @ HFT=0; Route 1_H

Toxic Gas Applications:

Random Integrity: SIL 1 @ HFT=0; Route 1_H Random Integrity: SIL 2 @ HFT=1; Route 1_H

PFD_{AVG} and Architecture Constraints must be verified for each application

Safety Function:

The Ultima XA, Ultima XE, and Ultima XIR Gas Monitors measure hazardous gas concentrations and communicate this level to a logic solver via an analog 4-20mA signal or alarm relays.

Application Restrictions:

The unit must be properly designed into a Safety Instrumented Function per the Safety Manual requirements.



John C. Jozallinas Evaluating Assessor

Certifying Assessor

Page 1 of 2

exida

Ultima XA, Ultima XE, and

Ultima XIR Gas Monitors

Cranberry Township, PA

MSA-The Safety

Company

USA

64 N Main St Sellersville, PA 18960

Certificate / Certificat / Zertifikat / 合格証

MSA 1202040 C001

Systematic Capability: SC 2 (SIL 2 Capable) Random Capability: Type B Element

Oxygen, Catalytic Combustible, IR Gas Applications:

Random Integrity: SIL 2 @ HFT=0; Route 1_H

Toxic Gas Applications: Random Integrity: SIL 1 @ HFT=0; Route 1_H

Random Integrity: SIL 2 @ HFT=1; Route 1_H

Systematic Capability:

The Product has met manufacturer design process requirements of Safety Integrity Level (SIL) 2. These are intended to achieve sufficient integrity against systematic errors of design by the manufacturer.

A Safety Instrumented Function (SIF) designed with this product must not be used at a SIL level higher than stated.

Random Capability:

The SIL limit imposed by the Architectural Constraints must be met for each element.

IEC 61508 Failure Rates in FIT*

| Device (with or without HART) | λ _{sp} | λ _{su} | λ _{DD} | λ _{DU} | SFF |
|--|-----------------|-----------------|-----------------|-----------------|-------|
| Ultima XA Series Gas Monitors, Oxygen, 4-20mA output | 0 FIT | 47 FIT | 4956 FIT | 459 FIT | 91.6% |
| Ultima XA Series Gas Monitors, Oxygen, relay output | 0 FIT | 73 FIT | 4965 FIT | 458 FIT | 91.7% |
| Ultima XA Series Gas Monitors, Toxic, 4-20mA output | 0 FIT | 48 FIT | 3337 FIT | 2102 FIT | 61.7% |
| Ultima XA Series Gas Monitors, Toxic, relay output | 0 FIT | 74 FIT | 3346 FIT | 2101 FIT | 61.9% |
| Ultima XA Series Gas Monitors, Catalytic, 4-20mA output | 0 FIT | 68 FIT | 5029 FIT | 435 FIT | 92.1% |
| Ultima XA Series Gas Monitors, Catalytic, relay output | 0 FIT | 75 FIT | 5023 FIT | 429 FIT | 92.2% |
| Ultima XE Series Gas Monitors, Oxygen, 4-20mA output | 0 FIT | 47 FIT | 4956 FIT | 459 FIT | 91.6% |
| Ultima XE Series Gas Monitors, Oxygen, relay output | 0 FIT | 73 FIT | 4965 FIT | 458 FIT | 91.7% |
| Ultima XE Series Gas Monitors, Toxic, 4-20mA output | 0 FIT | 48 FIT | 3337 FIT | 2102 FIT | 61.7% |
| Ultima XE Series Gas Monitors, Toxic, relay output | 0 FIT | 74 FIT | 3346 FIT | 2101 FIT | 61.9% |
| Ultima XE Series Gas Monitors, Catalytic, 4-20mA output | 0 FIT | 68 FIT | 5029 FIT | 435 FIT | 92.1% |
| Ultima XE Series Gas Monitors, Catalytic, relay output | 0 FIT | 75 FIT | 5023 FIT | 429 FIT | 92.2% |
| Ultima XIR Infrared Gas Detector, 4-20mA output | 0 FIT | 91 FIT | 862 FIT | 98 FIT | 90.7% |
| Ultima XIR Infrared Gas Detector, relay output | 99 FIT | 98 FIT | 715 FIT | 92 FIT | 90.8% |

* FIT = 1 failure / 10^9 hours

SIL Verification:

The Safety Integrity Level (SIL) of an entire Safety Instrumented Function (SIF) must be verified via a calculation of PFD_{AVG} considering redundant architectures, proof test interval, proof test effectiveness, any automatic diagnostics, average repair time and the specific failure rates of all products included in the SIF. Each element must be checked to assure compliance with minimum hardware fault tolerance (HFT) requirements.

The following documents are a mandatory part of certification:

Assessment Report: MSA 12-02-040 R001 V2R2

Safety Manual: 10100751, Rev 1 and higher

T-013, V3R9