MSA Miami Overspec Safety Spectacle **Specification Sheet**



Standard Hinge screw

Lens size diagonal: 61.2 mm	
Bridge: 15.2 mm	1 W
Temple length (lens-tip): 164 mm	
Overall Width (hinge-hinge): 144.5 mm	
Closest point between lens: 14 mm	
	1

Lens thickness: 2.3 mm

Lens size vertical: 44.8 mm

Lens Base: 6 Base

PD: 68 mm

Weight: 30 g

Screw

Lens options:

Temple length (lens-tip): 164 mm		
Overall Width (hinge-hinge): 144.5 mm		
Closest point between lens: 14 mm		
Closest point between temple tips: 80 mm		
COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 curve dual lens
Frama	Delveerbenete	Drawbar integral to frame

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 curve dual lens
Frame	Polycarbonate	Browbar integral to frame
Temples	Polycarbonate	Spatula

Stainless Steel

Clear and grey available

TEMPLES AND LENS OPTIONS	1	
Frame colors:	Same as lens	

Ş	SPECIAL FEATURES
	A Compact average accommodates most proscription glasses

- Compact overspec accommodates most prescription glasses. Full front, side and top protection with High Impact resistance.
- Flat temple design with light weight makes users more comfortable.
- Suitable for usage as visitor spectacle due to the affordable cost.
- 99.9% of harmful UV light can be blocked through the optical class one lens.
- Perfect and useful protective eyewear with high velocity impact resistance.

Meet ANSI Z87.1-2003 & CE EN166 standard