

Features

- Visitors/Overglasses spectacle for entry level
- For use over small to medium framed prescription spectacles
- Compact and stylish enough to wear without prescription spectacles
- Full front, side and top protection with high impact resistance
- TuffStuff anti-scratch coating according to EN 166 "K"
- Lens colours for indoor & outdoor applications: clear, smoke



Technical Specifications

General	
Weight	30 g
Temple length	164 mm
Overall width	144.5 mm
Lens thickness	2.3 mm
Lens base	6 base
Lens size	44.8 mm vertical, 61.2 mm diagonal
Material & Colours	
Lens	Polycarbonate Colours: clear, smoke Coating: TuffStuff anti-scratch
Temple	Polycarbonate
Frame	Polycarbonate
Screw	Stainless steel
Markings / Approvals	
Standard number	EN 166
Frame marking	MSA EN 166-FT CE
Lens marking	Clear: 2C-1.2 MSA 1 FT K CE Smoke: 5-2.5 MSA 1 FT K CE
Filter class	2C (Ultra violet radiation with enhanced colour recognition) 5 (Adequate protection against sun glare)
Scale number	1.2; Luminous transmittance ~89% clear 2.5; Luminous transmittance ~21% smoke
Optical class	1 (best class, for permanent wear)
Mechanical resistance	F (low energy impact 45 m/s) T (at extreme temperatures -5...+55°C)
Resistance to	K (surface damage by fine particles)
UV filter	99,9%

Ordering Information	
10145576	OverG, Clear, TuffStuff, 12x
10145577	OverG, Smoke, TuffStuff, 12x
Packaging	
Individual	1 pc in polybag with manual and EAN code39 as barcode
Box <i>MSA selling unit</i>	12 pcs with EAN code13 as barcode
Shipping carton	contains 12 boxes, with an EAN code128 as barcode

MSA Europe
Thiemannstrasse 1
DE-12059 Berlin
Phone +49 (0)30 68 86-0
Fax +49 (0)30 68 86-15 17
Email info.de@MSAsafety.com

Subject to change without notice. Rev00, 01.2013