

- **Economical**
- Available in 2 models
  - Residential Construction
    - Available in 3', 4', 5', and 6' lengths
    - Available with or without a steel, zinc plated D-ring
    - Meets all applicable OSHA regulations as well as ANSI A10.32 and ANSI Z359.1-2007
  - Concrete Construction
    - Available in 3', 4', 5', and 6' lengths
    - Includes protective sleeve
    - Available with or without a steel, zinc plated D-ring
    - Meets all applicable OSHA regulations as well as ANSI A10.32 and ANSI Z359.1-2007

## Durable

- 1¾" Polyester Webbing
- 5000 pound minimum breaking strength (22.2 kN)
- 100% proof tested to 3600 lbs (16 kN)
- 400-pound working capacity (182 kg)





Anchorage connector strap provides a secure point of attachment for residential or concrete construction application. Install in seconds; when finished, cut the protruding strap and discard.





Install the PointGuard Conrete Anchorage Strap by sliding the sewn loop onto the rebar before pouring the concrete form. Allow concrete to cure before using the PointGuard Strap as an anchorage point.

## **PointGuard Anchorage Connector Strap Ordering Information**

Part No	o. Description
100427	PointGuard Residential Anchorage Strap, 3', D-ring, Polyester
100427	93 PointGuard Residential Anchorage Strap, 3', Polyester
100805	15 PointGuard Residential Anchorage Strap, D-ring, 4'
100805	16 PointGuard Residential Anchorage Strap, D-ring, 5'
100805	17 PointGuard Residential Anchorage Strap, D-ring, 6'
100805	12 PointGuard Concrete Anchorage Strap, D-ring, 3'
100427	94 PointGuard Concrete Anchorage Strap, 4', D-ring, Polyester
100427	95 PointGuard Concrete Anchorage Strap, 4', Polyester
100805	13 PointGuard Concrete Anchorage Strap, D-ring, 5'
100805	14 PointGuard Concrete Anchorage Strap, D-ring, 6'
• • • • • • • • • • • • • • • • • • • •	

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 2300-50-MC / Nov. 2010 © MSA 2010 Printed in U.S.A.

Corporate Center

1000 Cranberry Woods Drive, Cranberry Township, PA 16066 USA Phone 412-967-3000 www.MSAnet.com

**U.S. Customer Service Center** 1-800-MSA-2222 1-800-967-0398

MSA Canada

Fax

1-800-672-2222 Phone

MSA Mexico

52-55 21 22 5770 Phone 52-55 5359 4330 Fax

MSA International

Phone 412-967-3354 412-967-3451 Offices and representatives worldwide

For further information:

