

PremAire® Combination

Combination Airline Escape Respirator



*Because every life has a **purpose...***



Pressure Reducer & Cylinder

A streamlined design combining the cylinder valve, cylinder gauge and first stage pressure reducer in one piece. A hard cover for this assembly ensures additional protection against accidental hits/drops while serving as a convenient handle.



Hip Belt & Shoulder Harness

The belt and shoulder harness assembly provides increased comfort while easily allowing the repositioning of the air cylinder from the right hip to left or any other comfortable position, without the need of doffing the whole device (relieving stress points).



Holster Carrier

The holster carrier secures the air cylinder while allowing easy detaching/attaching of the cylinder when needed. For users working in confined space this feature allows high maneuverability in tight places and simplifies entry and exit from confined space access.



Automatic Switch Valve

The Automatic Switch Valve (ASV) is mandatory for supplied air respirators with airline connection and for devices which need to be approved to EN 14593-1. In case the external air source fails or the pressure drops to 4.3–5.3 bar, the valve switches automatically to supply air from the PremAire Combination compressed air cylinder. If the pressure of the main air supply again rises above 5.3–6.5 bar, the valve switches back to the external air source.



Ordering Information

PremAire Combination Airline/Escape	
10222823	PremAire Combination Airline/Escape, with 3S full face mask, 2L composite cylinder (empty)
10222824	PremAire Combination Airline/Escape, with 3S full face mask, 2L steel cylinder (empty)

Accessories	
10127956-SP	PremAire QuickFill Connector
10126349-SP	PremAire Combination Storage Case
10148378-SP	Leg Strap Assembly
10124537-SP	Extension Belt (PremAire Holster)




With the filling port fitted on the pressure reducer, all cylinder options can be conveniently filled by a 200 or 300 bar compressor without the need to detach the harness assembly or cylinder.

Technical Specifications

Full Face Mask	NBR
Belt & Shoulder Harness	Polyester fabric mix
Air Cylinder	2.0L composite or 2.0L steel
Weight (approx.) ready for use with 3S mask and 2L composite cylinder	5kg for composite cylinder version 7kg for steel cylinder version
Nominal Duration Time (at 300 bar)	15 mins
Operating Pressure	300 bar (also 200 bar)
Operating Temperature	-40 °C to +60 °C
Approvals	EN 402 EN 14593-1

Applications

- Oil & Gas
- Chemical & Petrochemical
- Confined Space
- Tank Cleaning
- Hazardous Materials
- Firefighting Operations



Your direct contact

MSA Indonesia
Komplek Rukan Puri Mutiara
Jl. Griya Utama Blok BC 1 & 2,
Sunter Agung
Jakarta Utara,
DKI Jaya 14350
Indonesia
Phone +62 (21) 640 9000
Fax +62 (21) 641 2831

MSA Safety Malaysia Sdn Bhd
No.22, Jalan PPU ZA,
Taman Perindustrian Puchong Utama,
47100 Puchong,
Selangor, Malaysia
Phone +603-9767 8800
Fax +603-8051 8081
Email msa.malaysia@MSAsafety.com

MSA S.E. Asia Pte Ltd
35 Marsiling Industrial Estate Road 3
#04-01, Singapore 739257
Phone +65 6350 4500
Fax +65 6350 4505
Email msa.singapore@MSAsafety.com

MSA S.E Asia Pte Ltd. (Representative office)
Room 2036 SPACES Phahon 19 Building
No.1687/1 Phahonyothin Road Lad Yao Sub-district
Chatuchak District Bangkok 10900 Thailand
Phone +66 2038 8023
Fax +66 2617 8214
Email msa.thailand@MSAsafety.com