

MODEL S4100C HYDROCARBON GAS TRANSMITTER



S4100C- 1 2 - 0 - 1 - 1

HYDROCARBON SMART TRANSMITTER:

(Std) S4100C Hydrocarbon Smart Transmitter

A. COMBUSTIBLE-SENSOR:

- 00- NO SENSOR (SENSOR STOPPING PLUG NOT PROVIDED)
- 99- REMOTE ONLY, NO SENSOR REQUIRED
- 12- (Std) 11159-1 SENSOR STAINLESS STEEL STANDARD INDUSTRIAL HC ATEX
- 14- 11159-2 SENSOR STAINLESS STEEL HI-TEMP HC ATEX

B. COMBUSTIBLE-HOUSING:

- 0- (Std) NONE
- 1- B13-020-1 ATEX POLYESTER HOUSING, 20 mm, TEMP 75C
- 2- B13-021-1 ATEX HI TEMP HOUSING, 20 mm, 180C
- 3- B13-020-2 GOST POLYESTER HOUSING, 20 mm, TEMP 75C
- 4- B13-021-3 GOST HI TEMP HOUSING, 20 mm, 180C

C. APPROVALS/LANGUAGE:

- 1- (Std) ATEX/ENGLISH
- 2- ATEX/FRENCH
- 3- ATEX/GERMAN
- 4- ATEX/ITALIAN
- 5- RUSSIAN WITH RUSSIAN NAMEPLATE
- 6- ATEX & BV/ENGLISH
- 7- ATEX & BV/FRENCH
- 8- ATEX & BV/ITALIAN

D. CABLE ENTRY:

- 1- (Std) 2 X 20 mm CABLE ENTRIES

NOTES:

1. If sensor 11159-2 is selected, housing type B13-021-1 (or B13-021-3) is required.