

MODEL S4100T H2S SMART TRANSMITTER



S4100T - 1 5 - 0 - 1

TRANSMITTER:

(Std) HYDROGEN SULPHIDE SMART TRANSMITTER

A. H2S-SENSOR:

- 00- NONE
- 99- REMOTE ONLY NO SENSOR REQUIRED
- 11- 51457-1 SENSOR STAINLESS STEEL ATEX H2S 0-100 ppm
- 13- 51457-5 SENSOR STAINLESS STEEL ATEX H2S 0-50 ppm
- 15- (Std) 51457-9 SENSOR STAINLESS STEEL ATEX H2S 0-20 ppm

B. H2S-HOUSING:

- 0- (Std) NONE
- 1- B14-020-1 POLYESTER HOUSING, 20mm, ATEX
- 2- B14-020-2 POLYESTER HOUSING, 20mm, GOST

C. APPROVALS/LANGUAGE:

- 1- (Std) ATEX/ENGLISH
- 2- ATEX/FRENCH
- 5- RUSSIAN W/RUSSIAN NAMEPLATE
- 6- ATEX & BV/ENGLISH
- 7- ATEX & BV/FRENCH

NOTES:

1. Detection range is field selectable.
2. Correct sensor must be fitted if changing range.