



GENERAL MONITORS
Protection for life.

H₂S SENSORS AND ACCESSORIES



Features

- Solid-state operation
- Highly selective -- does not respond to hydrocarbons
- Unaffected by over-range exposure
- Robust mechanical design
- Resistant to high humidity and wide range of ambient temperatures
- Specific sensors meet ISA-92.0.01 performance standard

Benefits

- Functions in the harshest environments
- Low risk of false alarms
- Reduces need for sensor replacement
- Vibration and shock resistant
- Suitable for worldwide use
- Agency approved to strict performance standards

Description

General Monitors' hydrogen sulfide (H₂S) sensors are solid state devices, designed and manufactured for long life and fast response. They are selective to H₂S and remain unaffected by high concentrations of other substances like hydrogen, sulfur dioxide, and gasoline vapors, which are often present in facilities that process sour gas and crude oil.

A semiconductor device measures changes in electrical conductivity in a thin metal oxide film as a result of gas exposure. The change in conductivity is logarithmically correlated to the target gas concentration and used to supply a signal to the controller. The surface temperature of the film is maintained well above 100°C to reduce effects of ambient temperature, humidity and improve selectivity.

Metal oxide semiconductor (MOS) sensors are an essential component of General Monitors' line of intelligent sensors and control card-based H₂S detection systems. The sensors are easy to install and can be conveniently calibrated by using ampoules or disposable canisters of pre-mixed H₂S with dry air. Several accessories extend the usefulness of these sensors by protecting them against water and dust or facilitating their installation in ducts and sampling systems.

A high tolerance to a broad range of temperatures and humidity enable these sensors to operate in rugged environments, as does their capacity to withstand exposure to high H₂S concentrations over short periods.

The MOS sensors have been installed in extreme environments from the Saudi Arabian desert to the North Slope of Alaska.

Global sensor certifications include ATEX, CSA, FM, IECEx, and Russian approvals. Additionally, specific sensors conform to performance standard ISA-92.0.01.

Applications

- Chemical Plants
- Compressor Stations
- Gas Turbines
- LNG Plants
- Oil and Gas Exploration and Production
- Oil Refining
- Sewage and Water Treatment Plants
- Sulfur Recovery Plants

H₂S SENSORS

Sensor Selections

General Monitors' semiconductor sensors are available in three concentration ranges and in aluminum or stainless steel bodies. The sensors' ambient temperature ranges vary according to regulatory approval.

Part Number	Range (ppm)	Material	Certifications
50445-1	0-100	Aluminum	CSA, FM
50445-5	0-50	Aluminum	CSA, FM
50445-9	0-20	Aluminum	CSA, FM
50448-1	0-100	Stainless Steel	CSA, FM
50448-5	0-50	Stainless Steel	CSA, FM
50448-9	0-20	Stainless Steel	CSA, FM
51457-1	0-100	Stainless Steel	ATEX, CSA, IECEx, GOST-R
51457-5	0-50	Stainless Steel	ATEX, CSA, IECEx, GOST-R
51457-9	0-20	Stainless Steel	ATEX, CSA, IECEx, GOST-R
51457-1L	0-100	Stainless Steel, Lugs	ATEX, CSA, IECEx, GOST-R
51457-5L	0-50	Stainless Steel, Lugs	ATEX, CSA, IECEx, GOST-R
51457-9L	0-20	Stainless Steel, Lugs	ATEX, CSA, IECEx, GOST-R

Sensor Specifications

Type: Metal Oxide Semiconductor (MOS)

Response Time: With wire screen flame arrester:
T₅₀<14 seconds

With sintered stainless steel flame arrester: T₅₀<30 seconds

On application of full scale gas according to ANSI/ISA-92.0.01

Temperature Range: CSA: -40°F to +167°F
(-40°C to +75°C)

FM: -40°F to +140°F
(-40°C to +60°C)

ATEX / IECEx: -40°F to +248°F
(-40°C to +120°C)

Life: 3 - 5 years

Electrical Classification: Class I, Div. 1, Groups B, C, and D;
Ex d IIC

Warranty: 2 years

Sensor Housings:



P/N 10252-1, CSA, FM approved, explosion-proof housing



P/N B14-020-1, ATEX approved, polyester increased safety housing (P/N B14-020-2 GOST approved)



Model S4000TH Intelligent Gas Detector



Model S4100T Intelligent Gas Detector



Splash Guard (P/N 10395-1)

The Splash Guard prevents water from entering the sensor cavity and affecting the element response and also acts as an effective windscreen. Constructed of rugged ABS plastic and threaded for simple screw-on installation, the Splash Guard has a series of internal baffles to deflect water down and away from the sensor.

Dust Guard (P/N 10110-1)

The General Monitors Dust Guard Assembly prevents dust and other particulate matter from reaching the sensor flame arrestor and affecting the sensor response. The Dust Guard is also available in a kit with twelve disposable screens (P/N 10044-1).

Ampoules of H₂S (P/N 50004-x)

These glass ampoules are manufactured under strict quality control for use with the field calibrator and are available in a range of concentrations.

Sintered Stainless Steel Dust Guard (P/N 1800822)

The General Monitors Sintered Stainless Steel Dust Guard protects the sensor from fine particulates. It should be used only in dry environments because the sintered disc has a tendency to absorb water and act as a gas diffusion barrier until it dries out. For accurate calibration, the sensor should be calibrated with the guard in position.

Sensor Flow Chamber (P/N 10066)

The Sensor Flow Chamber is constructed of aluminum and is designed to be inserted into a sampling system.

Duct Mounting Plate (P/N 10041-1)

The Duct Mounting Plate is ideally suited to mount sensors for the monitoring of ducted air for living quarters in large offshore modules.

Field Calibrator (P/N 50000)

The General Monitors Field Calibrator (also referred to as a breaker bottle) provides a simple and efficient means of calibrating H₂S in the field. It consists of a plastic jar fitted with a removable lid and a seal which fits over the sensor. After an H₂S ampoule is placed in the ampoule holder, the screw assembly acts as a vice and breaks the ampoule releasing the gas for calibration purposes.



Field Calibrator and Ampoules



H₂S

ACCESSORIES

The H₂S Portable Purge Calibrator is a compact, practical, accurate and safe system for field calibration of H₂S sensors. The cylinder is filled with an H₂S in air mixture in one of six separate parts per million (ppm) levels of concentration (10, 20, 25, 35, 50, or 100). Using a known air/gas mixture reduces the possibility of error in field calibration.

The Portable Purge Calibrators are lightweight assemblies that are easy to carry. However, an optional carrying case is available for those desiring to carry more than 1 assembly at a time. The case can hold up to 2 complete assemblies and facilitates transporting them in the field.

Note: General Monitors recommends using ampoules for calibrating H₂S gas detection instruments. The H₂S Portable Purge Calibrator is available for applications where a calibration method of flowing H₂S gas to the sensor might provide a better calibration source (e.g. high humidity environments).

Specifications

Regulator

Flow Rate: 200 milliliters per minute
(12.2 cubic inches per minute)

Temperature

Range: -40°F to 130°F
(-40°C to 54°C)

Storage Humidity

Range: 5% to 100% RH non-condensing

Weight: Assembly 5 lbs.
Cylinder 3 lbs.
Case 4 lbs.

Cylinder

Length: 13.5 inches

Cylinder

Diameter: 3.5 inches

Specifications subject to change without notice.



Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
Email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
Email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
Email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8143814
Fax: +971-4-8857587
Email: gmme@generalmonitors.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk