V-Gard® **Visor Comparison**



,	V-Gard Visor	P/N	Dimensions L x W x Thickness	Visor Type	Fits with Earmuffs	Works with Chin Protector ¹	Impact	Anti-Scratch	Anti-Fog	UV	Tinted	Welding (Shade)	Arc	Elevated Temp	Chem-Resistant ²
					68					÷'nv	60				•••
	MESH, PLASTIC EDGE	10116557	8.0" x 17.0"												
	MESH, PLASTIC EDGE, NITROMETER	10116558	8.0" x 17.0" (+~3" for Chin Protector)												
	MESH, ALUMINUM	10158822	8" x 16.5" x 0.1"												
	CLEAR, PC, CONTOURED ³	10115836	8" x 17.0" x 0.04"	PC											
	CLEAR, PC, CONTOURED, NITROMETER	10115837	8" x 17.0" x 0.04" (+~3" for Chin Protector)	PC											
OSE	CLEAR PC, CONTOURED	10115840	8.0" x 17.0" x 0.06"	PC											7
AL PURP	CLEAR, PC, CONTOURED, AF/AS	10115839	8.0" x 17.0" x 0.06"	PC											
GENER	CLEAR, PC, CONTOURED, NITROMETER, AF/AS	10115841	8.0" x 17.0" x 0.06" (+~3" for Chin Protector)	PC											
	GREEN TINT⁴, PC, CONTOURED, AF/AS	10115842	8.0" x 17.0" x 0.06"	PC											
	CLEAR, PC, CONTOURED	10115863	9.5" x 17.0" x 0.04"	PC											
	CLEAR PC, NITROMETER, NON-CSA	10117783	8.0" x 17.0" x 0.06" (+~3" for Chin Protector)	PC											
	CLEAR PC	10115853	10.375" x 17.0" x 0.098"	PC	(
	GREEN TINT⁴ PC	10115854	10.375" x 17.0" x 0.098"	PC											

¹ Chin Protector size noted is V-Gard Retractable Chin Protector.

² Please consult the Chemical Application Quick Reference Guide or call MSA Customer Service for additional information on the types of chemicals resisted by specific visors.

³ This product available in a bulk pack of 20 (PN 10120108).

⁴ Not for use where a Shade Infrared (IR) visor is required.

V-Gard Visor	P/N	Dimensions L x W x Thickness	Visor Type	Fits with Earmuffs	Works with Chin Protector ⁵	Impact	Anti-Scratch	Anti-Fog	UV	Tinted	Welding (Shade)	Arc	Elevated Temp	Chem-Resistant ⁶
				68					÷'nv	60	<u>;/</u>	<u></u> NFPA 70E		• ••
CLEAR PROPIONATE	10115855	8.0" x 17.0" x 0.098"	PROP											?
CLEAR PROPIONATE, NITROMETER	10115856	8.0" x 17.0" x 0.098" (+~ 3" for Chin Protector)	PROP		(Ø								
CLEAR PROPIONATE	10115851	9.25" x 18.0" x 0.098"	PROP			(
CLEAR PC	10115844	9.25" x 17.0" x 0.098"	PC			•			?					?
GREEN TINT ⁷ PC	10115845	9.25" x 17.0" x 0.098"	PC			(Ø				Ø
REFLECTIVE COATED, CLEAR PC	10115848	9.5" x 17.75" x 0.07"	PC			(
REFLECTIVE COATED, GREEN TINT ⁷ PC	10115850	9.5" x 17.75" x 0.07"	PC			((
SHADE 3 IR, PC	10115859	8" x 17.25" x 0.07"	PC			(
SHADE 3 IR, PC, NITROMETER	10115860	8" x 17.25" x 0.07" (+~3" for Chin Protector)	PC		((
SHADE 5 IR, PC	10115861	8" x 17.25" x 0.07"	PC											
SHADE 5 IR, PC, NITROMETER	10115862	8" x 17.25" x 0.07" (+~3" for Chin Protector)	PC		€	(
SPECIAL TINT ¹¹ , PC, ARC	10115847	9.25" x 18.0" x 0.065"	PC							10		12.9 cal/cm ²		
SPECIAL TINT ¹ , PC, ARC, NITROMETER w/ CHIN PROTECTOR	10118480	8" x 17.25" x 0.065" (+2" for Standard Chin Protector)	PC		9					10		11.3 cal/cm ²		

- $^{5} \ \ Chin \, \textit{Protector size is V-Gard Retractable Chin Protector, except as noted on the Arc Nitrometer.}$
- Please consult the Chemical Application Quick Reference Guide or call MSA Customer Service for additional information on the types of chemicals resisted by specific visors.
- Not for use where a Shade Infrared (IR) visor is required.
- ⁸ Visor not coated with heat reflective material. Not recommended for use in most radiant heat environments.
- ⁹ Sold with V-Gard Standard Chin Protector, which must be worn to achieve calorie ratings.
- ¹⁰ Designated Special Purpose (S) under ANSI/ISEA Z87.1-2010. Not for welding, cutting or brazing applications.
- 11 DO NOT use with V-Gard Headgear. These visors are designated for use with specified V-Gard Frames and MSA helmets ONLY as face protection for workers exposed to high voltage electric arcs. V-Gard Headgear has not been tested or certified to the Test Method, and should not be used for this type of Arc Flash protection.

NOTE: This chart is provided as a guide only to visor selection. The proper personal protective equipment should be selected for use and application by the site safety specialist, whose responsibility is that hazards, communication of instructions, precautions and limitations are conveyed and observed.

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 0670-004-MC / August 2016 © MSA 2016 Printed in U.S.A.

MSA – The Safety Company 1000 Cranberry Woods Drive Cranberry Township, PA 16066 Phone 724-776-8600 www.MSAsafety.com

 U.S. Customer Service Center

 Phone
 1-800-MSA-2222

 Fax
 1-800-967-0398

MSA Canada Phone 1-800-672-2222 Fax 1-800-967-0398

MSA Mexico Phone 01 800 672 7222 Fax 52-44 2227 3943

For more information visit www.MSAsafety.com Keyword: VGardSystem or call Customer Service 1.800.MSA.2222

KEY CODE						
Code	Description					
PC	Polycarbonate					
PROP	Propionate Aluminum (edge/trim material)					
ALUM						
PLST	Plastic (edge/trim material)					
AFAS	Anti-fog and anti-scratch coatings					
REFLECTIVE	Coated for elevated temp use					
CLR	Clear					
GN	Green tint					
SH3/SH5	Shade 3 or 5 IR					
CHN	For use with V-Gard Chin Protectors					
LTW	Lightweight (0.04" thick)					





