

MSA


The Safety Company

Workman 30' Self-Retracting Lanyard

Model / Modelo / Modèle	10119507
Line Length / Largo de la línea / Ligne de longueur	30FT
Material / Material / Matériel	Galvanized Cable
Serial Number / Número de serie / Numéro de série	1234567890
Date Made / Fecha de fabricación / Date de fabrication	2011-5-30
Meets Standards / Cumple las normas / Satisfait aux normes	CSA Z259.2.2-Type2 ANSI A10.32-2004 ANSI Z359.1 OSHA



112 Rev.0 10119836




MSA Workman® Self-retracting Lanyard

With lightweight design, durable thermoplastic housing and impact-absorbing bumpers, the Workman SRL will not only be accepted by users, but also provides years of dependable service. The Workman SRL features:

- RFID-enabled product for simplified product tracking and inspection.
 - 400-lb working capacity for increased versatility.
- Integral, ergonomic carrying handle for easier transport and installation.
- Available with galvanized or stainless steel lifeline to fit your varied applications.
- Swivel snaphook with load indicator at lifeline end greatly limits twisting of cable; also alerts users that the Workman SRL has been involved in a fall.
 - Available in 30-ft length to provide the mobility you need.
 - Certification to A10.32, ANSI Z359.1-2007 and CSA Z259.2.2 for compliance and peace of mind. Meets all OSHA requirements.





MSA Workman® Self-retracting Lanyard Features and Benefits

Integral, ergonomic
carrying handle for
easier transport and
installation.


Impact-absorbing
bumpers provides
years of dependable
service.

RFID-enabled product
for simplified product
tracking and inspection.

Recessed labels
provide increased
durability and
service life.

Swivel snaphook with
load indicator at lifeline
end greatly limits
twisting of cable; also
alerts users that the
Workman SRL has been
involved in a fall.





MSA Workman®

Self-retracting Lanyard

Product Specification

Materials

- Housing:** Impact-resistant thermoplastic
- Bumpers:** Impact-absorbing thermoplastic rubber
- Frame:** Alloy steel
- Hub:** Cast aluminum
- Locking Mechanism:** Alloy steel
- Lifeline:** 3/16" (5mm) diameter, galvanized steel or stainless steel cable
- Snaphook:** Steel with 3,600-lb gate strength

Technical

- Maximum Working Load:** 400 lbs (181kg)
- Minimum Breaking Strength:** 3000 lbs (13.3kN)
- Lifeline Tension:** Starts at 1.5 lbs (6.7N)
- Maximum Arresting Distance:** 54" (1.4m) for workers 311 - 400 lbs (142kg - 181kg)
- Average Arresting Force:** 900 lbs (4kN) for workers 75 - 310 lbs (34-141kg) and under
1800 lbs (8 kN) for workers 311 - 400 lbs (142kg - 181kg)
- Weight:** 10 lbs
- Line Length:** 30 ft (10m)

Certification

- This product meets or exceeds the following standards:** OSHA: 1926.502, 1910.66
ANSI: A10.32, ANSI Z359.1-2007
CSA: Z259.2.2



For more information on MSA products,
check out these two great resources:



MSA-U® Training Center is a feature-rich online training center offering programs on MSA products, product technologies, and safety industry standards. www.MSAafety.com/msau



MSA TV offers a wide variety of informative videos on our products. So log in, lean back, and learn!

MSA Corporate Center

1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAafety.com

U.S. Customer Service Center

Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada

Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Mexico

Phone 01-800-672-7222
Fax 52-44-2227-3943

MSA International

Phone 724-776-8626
Toll Free 1-800-672-7777
FAX 724-741-1559

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 2301-107-MC / Feb 2012

© MSA 2012 Printed in U.S.A.



The Safety Company