

Workman[®] and Dynevac[®] II Rescuers



*Because every life has a **purpose...***

Workman Rescuer

Fast, easy and intuitive fall protection with integral bi-directional retrieval capability. Fast installation and setup; exclusive integral bracket uses existing tripod pin. Can be used as a stand-alone retractable device, as the carrying handle may be used as an anchorage attachment.

Standard features:

- User capacity up to 400 lbs. for personnel
- Stainless steel 3/16" wire rope
- Integral mounting bracket
- Color-coded switch for retrieval mechanism activation
- Ergonomic, stainless steel carrying handle can also be used as anchorage connection point
- Built-in shock absorber
- Robust aluminum housing with thermoplastic bumpers
- Self-locking swivel snaphook with load indicator
- Stow-able, foldable crank handle
- RFID-enabled
- Available in Synthetic Rope
- Meets all applicable OSHA regulations, ANSI Z359.14 and CSA Z259.2.2

			ANSI	CSA
WORKMAN RESCUER	10158178	Workman Rescuer, stainless steel cable, 50 ft. (15m)	■	
	10158180	Workman Rescuer, stainless steel cable, 50 ft. (15m)		■
SYNTHETIC RESCUER	10159755	Workman Rescuer, synthetic rope, 50 ft. (15m)	■	

Specifications

- **Net weight**
16.3kg (includes bracket)
- **Crank handle material**
Carbon steel with zinc plating
- **Housing material**
Cast aluminum
- **Lifting and lowering gear ratio**
Gear ratio: 5:1
- **Maximum free fall distance**
2 ft. (0.6m)
- **Maximum deceleration distance**
54" (1.4m)
- **Maximum arresting force**
1800 lbs. (8Kn)



Workman Rescuer
Part No. 10158178

Dynevac II Self-Retracting Lanyard, Field-Resettable Model

- Emergency retrieval capabilities
- Switch from fall arrest to retrieval modes quickly and simply
- Allows user to reset device in the field from retrieval mode to fall arrest mode
- Simple operation—ready for immediate emergency retrieval
- After fall arrest or retrieval—unit may be reused following competent person inspection
- Provides fall arrest and emergency lifting and lowering for confined space entry
- Available in 50-ft. and 95-ft. line lengths
- Built-in shock absorbing mechanism limits fall arrest forces
- Meets all applicable OSHA regulations, and Z359.14 and CSA as noted in chart below

Specifications

- 4.5-ft. per second locking speed and built-in shock absorber
- 3/16" stainless steel cable
- Forged steel, zinc-plated self-locking swivel snaphook with load indicator
- 3 cam driven, independent braking mechanisms prevent freezing in icy or corrosive conditions
- Average lifting speed of 25-ft. per minute

			ANSI	CSA
DYNEVAC II SELF-RETRACTING LANYARDS	10007782	50' (16m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line		■
	10007783	95' (30m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line		■
	10127293	50' (16m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line	■	
	10127295	95' (30m) Self-Retracting Lanyard with Emergency Rescuer, 3/16" diameter stainless steel line	■	



Dynevac II SRL with
Emergency Rescuer
Part No. 10127293

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA - The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAsafety.com
U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-MSA-2222
Fax 1-800-967-0398
MSA Mexico
Phone 01 800 672 7222
Fax 52-44 2227 3943