



MSA's Workman Rescuer provides fast, easy and intuitive fall protection with integral bi-directional retrieval capability. Not only does the Workman Rescuer arrest the fall, its retrieval capability allows the fallen worker to ascend or descend to a safe location. This durable, economical addition to the Workman Series of products offers fast installation and setup, ideal for applications where time and ease of use are a priority. The Workman Rescuer is also a stand-alone retractable device, as the carrying handle may be used as an anchorage attachment.

Workman® Rescuer: Ease of Use, Many Applications

Exclusive integral bracket uses existing tripod pin, leaving fewer components to attach or become damaged or misplaced. Fall protection/retrieval mode knob simply pulls and rotates to activate. Use this device as a component of a confined space system for one application and as a standard self-retracting lanyard for another.

- Experienced and novice users will learn setup and operation quickly and effectively
- Comparable size and weight to competitive products
- Great for OGP turnarounds, construction, utilities, and other confined space applications
- QR code on product label offers instant access to setup video and additional information

Features & Benefits

The Workman Rescuer offers these standard features:

- User capacity up to 140kg for personnel
- Stainless steel 3/16" wire rope
- Integral mounting bracket
- Colour-coded switch for retrieval mechanism activation
- Ergonomic, stainless steel carrying handle can also be used as anchorage connection point
- Built-in shock absorber
- Robust aluminium housing with thermoplastic bumpers
- Self-locking swivel snaphook with load indicator
- Stow-able, foldable crank handle
- RFID-enabled
- Certified to EN 360 and complies with AS/NZ 1891.3

Specifications

- **Net weight**
16.3kg (includes bracket)
- **Crank handle material**
Carbon steel with zinc plating
- **Housing material**
Cast aluminium
- **Lifting and lowering gear ratio**
Gear ratio: 5:1
- **Maximum free fall distance**
0.6m
- **Maximum deceleration distance**
1.4m
- **Maximum arresting force**
6kN

Ordering Information

Part Number	Description
10158192	Workman Rescuer, stainless steel cable, 15m



Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

MSA – The Safety Company
11 Columbia Way
Norwest Business Park
Baulkham Hills NSW 2153
Phone 61 2 9688 0333
Customer Service
Phone 1300 728 072
Email aus.customerservice@MSAsafety.com
www.MSAsafety.com

MSA New Zealand
Customer Service
Phone 0800 441 335
Email nz.customerservice@MSAsafety.com
www.MSAsafety.com