# Workman® Winch





The Workman Winch is rugged, versatile and economical for lifting, lowering and positioning of personnel and materials within confined space applications. Designed for maximum 140 kg workload for personnel and 225 kg for materials, the Workman Winch is built with tough thermoplastic housing to ensure high performance within the harshest environments. Winch offers integral, ergonomic carry grip and unique, foldable handle for simple storage. Patent-pending bracket design allows for easy, rapid assembly.



## Features & Benefits

#### All Workman Winches have several standard features:

- Rated working load 140 kg for personnel and 225 kg for materials
- An open drum wound with 5 mm cable
- Built-in shock absorber
- Clutched drive to prevent winch overload and reduce the possibility of injury to a person if caught on a structural member during lifting
- Double-braking system
- Robust plastic housing and mounting bracket
- Self-locking swivel snaphook
- Manual foldable crank handle
- Level wind mechanism for a tangle-free cable drum
- RFID-enabled

## Specifications

| Maximum working load                 | Personnel: 140 kg<br>Materials: 225 kg |
|--------------------------------------|--|
| Line diameter                        | Cable: 5 mm                            |
| Minimum line strength                | Cable: 14.7 KN                         |
| Net weight with 20 m of line         | Cable: 12.8 kg                         |
| Swivel snaphook gate opening         | 21 mm                                  |
| Crank force to lift 400 lbs (181 kg) | 133 N                                  |
| Cranking diameter                    | 56 cm                                  |
| Avg. lifting speed<br>181 kg load    | 4 m/min                                |

## Ordering Information

| Part Number | Description                                |
|-------------|--|
| 10147296    | Workman Winch, Stainless Steel Cable, 20 m |
| 10154688    | Workman Winch, Stainless Steel Cable, 30 m |



Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

 MSA – The Safety Company
 M

 11 Columbia Way
 Ct

 Norwest Business Park
 Pf

 Baulkham Hills NSW 2153
 Er

 Phone
 61 2 9688 0333
 W

 Customer Service
 Phone
 100 728 072

 Email
 aus.customerservice@MSAsafety.com
 WW.MSAsafety.com

MSA New Zealand Customer Service Phone 0800 441 335 Email nz.customerservice@MSAsafety.com www.MSAsafety.com