

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2018/03/26

n. 769181306/OE

Validity: from 2018/04/21 to 2023/04/20

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	CARHARTT BV Cruquiusweg 109-D – 1019 AG, Amsterdam (THE NETHERLANDS)
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II: "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	"F702903.001"
Description:	<u>model</u> : B (ankle boot); <u>fastening system</u> : by means of laces; <u>processing</u> : direct injection; <u>outsole</u> : black rubber RANGER with yellow stamp VIBRAM marked "ANTISTATIC OII RESISTANT HRO-HI" (cod. 3040BN/00-RAS/1/00); <u>midsole</u> : black-coloured PU foam (cod. MPI/001); <u>upper</u> : black leather DAKAR Trekking CE declared thickness 2.0/2,2 (cod. DAC/NER) with inserts made of black fabric TECNIC in the quarter/collar area (cod. TLP/1081) and inserts made of black diamond water-resistant leather declared thickness 1.8/2,0 mm on both the tip and heel area (cod. DII/NER); <u>collar</u> : black water-resistant leather (cod. PID/NER); <u>tongue</u> : same leather as that of the upper, centrally lined and padded and same leather as that of the collar in the upper area; <u>bellows</u> : black coated fabric ANDREA SILVIA (cod. ANS/NER); <u>vamp lining</u> : black non-woven material AITELLE coupled with MTP4 D40 and black knit CHARMEUSE (cod. FCA/NEC); <u>rear lining</u> : black three-dimensional fabric article AT 488 SPECIAL (cod. A8S/NER); <u>heel-grip</u> : black microfiber article MICROLIM 0.8 SCAMOSCINA (cod. MI8/NER); <u>collar and upper tongue lining</u> : black leather (cod. PEL/NER); <u>insole</u> : white multi-layered fabric ZP03/1500 (cod. LC/ZP03) with a green stamp covered by the lining, <u>which also serves as penetration-resistant insert</u> ; <u>removable insock</u> : thermo-formed, made of black agglomerated material with c
<u></u>	heel zone, coupled with black/silver fabric in contact with the foot (cod. FM126NA); <u>toe-cap</u> : glass fiber article 604 CONTENDER (cod. 604FV).
Technical Standard:	EN ISO 20344:2011Personal protective equipment – Test methods for footwear(UNI EN ISO 20345:2011 (UNI EN ISO 20345:2012)Personal protective equipment – Safety footwear
Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.
Size range:	From 39 to 48
Technical File:	DC-9211/E
Test report:	RCT n°3712040.01/E





PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Validity: Date: 2018/03/26 n. 769181306/OE from 2018/04/21 to 2023/04/20 Functions and basic requirements for safety footwear (see Table 2 and 3 of EN ISO 20345:2011): performance levels: all mandatory ones, among which: SRC = Slip resistance – meets the following requirement: - surface: ceramic / lubricant: detergent solution; - surface: steel / lubricant: glycerol. Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): **s3 =** closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; **HRO = re**sistance to hot contact of the outsole; **HI =** heat insulation of sole complex. NOTE: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption). Marking: on a stitched label and displaying the following information: - CE Marking; - Name/Trademark and complete address of the Manufacturer; - designation of the footwear (= alphanumeric code: unique/unambiguous); - nr. and year of the Technical Harmonized Standard of reference + safety symbols; - size of the footwear (also printed on the outsole); - production date (month + year); - additional information: internal codes. carbartt F702903.001 EN ISO20345:2011 01/2018 S3 HRO HI SRC XXXXXX 21434 702903c6 42 CARHARTT BV Cruquiusweg 109-D 19 AG Amsterdam. NL 1019

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

