

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2019/04/02

n. 769191404/OE

Validity: 2024/04/01

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	CARHARTT BV Cruquiusweg 109-D – 1019 AG, Amsterdam (TH <mark>E N</mark> ETHERLANDS)
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	"F702913.001"
Description:	model: A (low shoe); fastening system: by means of laces; processing: direct injection, sole: black rubber RANGER with a yellow stamp VIBRAM marked "OIL RESISTANT HRO-HI" (3040BN/00-RA\$/1/00); midsole: black foam PU (MPI/001); upper: black grain leather DAKAR TREKKING declared thickness 2,0-2,2 mm (DAC/NER), black leather DIAMANTE declared thickness 1,8-2,0 mm water-repellent (DII/NER); collar: black fabric TECNIC L. coupled with PE115 perforated (LPF/1081) and black leather "idro" (PID/NER); vamp lining: black non-woven material AITELLE 150 coupled with MTP4 D40 and black CHARMEUSE (FCA/NEC); rear lining: black non-woven material AITELLE 150 coupled with MTP4 D40 and black CHARMEUSE (FCA/NEC); rear lining: black three-dimensional fabric AT488 SPECIAL (A8S/NER); tongue: black fabric TECNIC L. coupled with PE40 (TLA/1081) and black leather "idro" (PID/NER), lined and padded; bellow: black coated fabric ANDREA SILVIA (ANS/NER), lined; heel-grip lining: black microfiber MICROLIM 0,8 SCAMOSCINA mounted from the reverse side (MI8/NER); collar and upper tongue lining: black leather (PID/NER); insole: white multilayered fabric ZP03/1500 (LC/ZP03) with green stamp, which also serves as penetration-resistant insert: removable insock: thermo-formed, in black agglomerated material with a reinforcement made of anthracite grey foam material from the forepart area to the heel zone, coupled with black/silver fabric in contact with the foot (FM126NA); toe-cap: glass fiber article 604 CONTENDER (604FV).
Technical Standard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012)Personal protective equipment – Test methods for footwearEN ISO 20345:2011 (UNI EN ISO 20345:2012)Personal protective equipment – Safety footwear
Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes
Size range:	from 39 to 48
Technical File:	DC-10476/E
Test report:	RCT n°3830929.02/E



Certificato ue E rev04 - 19/04/18



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2019/04/02

n. 769191404/OE

Validity: 2024/04/01



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).



Certificato ue E rev04 - 19/04/18