

## EU Type Examination Certificate

Date: 2019/04/02

n. **769191403/OE**

Validity:  
2024/04/01

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

|   |   |   |
|---|---|---|
| Manufacturer:<br>(Responsible of the PPE) | <b>CARHARTT BV</b><br>Cruquiusweg 109-D – 1019 AG, Amsterdam (THE NETHERLANDS)  |   |
| Type of PPE:                              | <b>Safety footwear</b> in conformity with <b>EN ISO 20345:2011 class I</b> (= footwear in leather and other materials)  |   |
| Category of PPE:                          | <b>II</b> : "medium" risks.<br>This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.  |   |
| Model                                     | <b>"F702913.201"</b>  |   |
| Description:                              | <p><u>model</u>: A (low shoe);<br/> <u>fastening system</u>: by means of laces;<br/> <u>processing</u>: direct injection,<br/> <u>sole</u>: black rubber RANGER with a yellow stamp VIBRAM marked "OIL RESISTANT HRO-HI" (3040B/00-RAS/1/00);<br/> <u>midsole</u>: "coffie" brown PU foam (MPI/001);<br/> <u>upper</u>: grain leather DAKAR TREKKING color burnt brown declared thickness 2,0-2,2 mm (DAC/BRU), black leather DIAMANTE, declared thickness 1,8-2,0 mm water-resistant (DII/NER);<br/> <u>collar</u>: dark brown fabric TECNIC L. coupled with perforated PE115 (code LPF/TMO) and otter-brown 04 leather "idro" (PID/LON);<br/> <u>vamp lining</u>: black non-woven material AITELLE 150 coupled with MTP4 D40 and black CHARMEUSE (FCA/NEC);<br/> <u>rear lining</u>: brown three-dimensional fabric AT488 SPECIAL (A8S/6009);<br/> <u>tongue</u>: dark brown fabric TECNIC L. coupled with a PE40 (TLA/TMO) and otter-brown 04 leather "idro" (PID/LON), lined and padded;<br/> <u>bellow</u>: black coated fabric ANDREA SILVIA (ANS/NER), lined;<br/> <u>heel-grip lining</u>: black microfiber MICROLIM 0,8 SCAMOSCINA mounted from the reverse side (MI8/NER);<br/> <u>collar and upper tongue lining</u>: in otter-brown 04 leather "idro" (PID/LON);<br/> <u>insole</u>: white multilayered fabric ZP03/1500 (LC/ZP03) with green stamp, <u>which also serves as penetration-resistant insert</u>;<br/> <u>removable insock</u>: thermo-formed, in black agglomerated material with a reinforcement made of anthracite grey foam material from the forepart area to the heel zone, coupled with black/silver fabric in contact with the foot (FM126NA);<br/> <u>toe-cap</u>: glass fiber article 604 CONTENDER (604FV).</p> |   |
| Technical Standard:                       | <b>EN ISO 20344:2011</b><br>(UNI EN ISO 20344:2012)   | Personal protective equipment – Test methods for footwear |
|   | <b>EN ISO 20345:2011</b><br>(UNI EN ISO 20345:2012)   | Personal protective equipment – Safety footwear           |
| Intended use:                             | general industry, engineering industry, agriculture, warehouses, works on trucks, cranes  |   |
| Size range:                               | from 39 to 48   |   |
| Technical File:                           | <b>DC-10476/E</b>   |   |
| Test report:                              | <b>RCT n°3830929.02/E</b>   |   |

## EU Type Examination Certificate

Date: 2019/04/02

n. **769191403/OE**

Validity:  
2024/04/01

Functions and performance levels:

**basic requirements for safety footwear** (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

**SRC = Slip resistance** – meets the following requirement:

- surface: ceramic / lubricant: detergent solution;
- surface: steel / lubricant: glycerol.

**Additional requirements** (Tab. 18 and 20 of EN ISO 20345:2011):

**S3** = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; **HRO** = resistance to hot contact of the outsole; **HI** = heat insulation of sole complex.

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking:

on a stitched label and displaying the following information:

- **CE Marking**;
- Name/Trademark and complete address of the Manufacturer;
- designation of the footwear (= alphanumeric code: unique/unambiguous);
- nr. and year of the Standard of reference + safety symbols;
- size of the footwear (also printed on the outsole);
- production date (month + year);
- additional information: internal codes.

**carhartt**  
F702913.201  
**CE** EN ISO20345:2011  
01 / 2019  
S3 HRO HI SRC

---

21434 XXXXXX  
702913c1  
42  
CARHARTT BV  
Cruquiusweg 109-D  
1019 AG Amsterdam, NL



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

