



Allegato a Certificato UE del Tipo

Annex to EU Type Certificate
Anhang zur EU-Baumusterprüfung Zertifikat
Annexe au Certificat UE de type

Data/Date/Datum/Date
03/11/2023

n. **769191401/***

Validità/Validity/Gültigkeit/Validité
01/04/2029

Azienda: **CARHARTT BV**
Company:
Unternehmen:
Compagnie:

Estensione di validità Certificato UE a seguito di rinnovo semplificato

Extension of EU Type Certificate validity due to simplified renewal
Weite der EU-Baumusterprüfungsgültigkeit durch vereinfachte Verfahren
Prolongation de la validité du Certificat UE de type en raison d'un renouvellement simplifié

Regolamento (UE) 2016/425 § 28

Regulation (EU) 2016/425 § 28
Verordnung (EU) 2016/425 § 28
Règlement (UE) 2016/425 § 28

Il presente documento estende la validità del Certificato UE n. 769191401/* al 01/04/2029

This document extends the validity of the EU Certificate n. 769191401/* to 01/04/2029
Dieses Dokument verlängert die Gültigkeit des EU-Zertifikats n. 769191401/* bis zum 01/04/2029
Ce document prolonge la validité du Certificat UE n. 769191401/* jusqu'au 01/04/2029

Commessa interna: **17656/E**

Internal order:
Innere Ordnung:
Commande interne:

/* lingua redazione documento, vedere originale
/* document's drafting language, see original
/* Redaktionsprache des Dokuments, siehe Original
/* langue de rédaction de documents, voir original



EU Type Examination Certificate

Date: 2019/04/02

n. **769191401/OE**

Validity:
2024/04/01

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	CARHART BV Cruquiusweg 109-D – 1019 AG, Amsterdam (THE NETHERLANDS)	
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)	
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.	
Model	"F702919.001"	
Description:	<p><u>model</u>: B (ankle boot); <u>fastening system</u>: absent (with lateral bands); <u>processing</u>: direct injection; <u>sole</u>: black rubber RANGER with yellow stamp VIBRAM marked "OIL RESISTANT HRO-HI" (3040BN/00-RAS/1/00); <u>midsole</u>: black foam PU (MPI/001); <u>upper</u>: black grain leather DAKAR TREKKING, declared thickness 2,0-2,2 mm (DAC/NER); <u>vamp lining</u>: black non-woven material AITELLE 150 coupled with MTP4 D40 and black CHARMEUSE (FCA/NEC); <u>rear lining</u>: black three-dimensional fabric AT488 SPECIAL (A8S/NER); <u>heel-grip lining</u>: black microfiber MICROLIM 0,8 SCAMOSCINA mounted from the reverse side (MI8/NER); <u>collar and upper tongue lining</u>: black leather (PEL/NER); <u>insole</u>: white multi-layered fabric ZP03/1500 (LC/ZP03) with green stamp, <u>which also serves as penetration-resistant insert</u>; <u>removable insock</u>: thermo-formed, in black agglomerated material with a reinforcement made of anthracite grey foam material from the forepart area to the heel zone, coupled with black/silver fabric in contact with the foot (FM126NA); <u>toe-cap</u>: glass fiber article 604 CONTENDER (604FV).</p>	
Technical Standard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012)	Personal protective equipment – Test methods for footwear
	EN ISO 20345:2011 (UNI EN ISO 20345:2012)	Personal protective equipment – Safety footwear
Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes	
Size range:	from 39 to 48	
Technical File:	DC-10553/E	
Test report:	RCT n°3830910.01/E	

EU Type Examination Certificate

Date: 2019/04/02

n. **769191401/OE**

Validity:
2024/04/01

Functions and performance levels:

basic requirements for safety footwear (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

SRC = Slip resistance – meets the following requirement:

- surface: ceramic / lubricant: detergent solution;
- surface: steel / lubricant: glycerol.

Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):

S3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; **HRO** = resistance to hot contact of the outsole; **HI** = heat insulation of sole complex.

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking:

on a stitched label and displaying the following information:

- **CE Marking**;
- Name/Trademark and complete address of the Manufacturer;
- designation of the footwear (= alphanumeric code: unique/unambiguous);
- nr. and year of the Standard of reference + safety symbols;
- size of the footwear (also printed on the outsole);
- production date (month + year);
- additional information: internal codes.

carhartt
F702919.001
CE EN ISO20345:2011
02 / 2019
S3 HRO HI SRC

21434 XXXXXX
702919c1
42

CARHARTT BV
Cruquiusweg 109-D
1019 AG Amsterdam, NL



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).