

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2022/05/20

## n. 769222001/OE

Validity: 2027/05/19

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	<b>CARHARTT BV</b> Cruquiusweg 109-D – 1019 AG, Amsterdam (THE NETHERLANDS)		
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)		
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model	"F705159.201"		
Description:	<u>model</u> : B (ankle boot); <u>fastening system</u> : by means of laces; <u>processing</u> : direct injection; <u>outsole</u> : para brown color marked "oil resistant hi src hro" with yellow "VIBRAM" stamp on the plantar arch area (2172BAV/00 – 6306/76/00); <u>midsole</u> : ivory color foam PU (MPI/001); <u>reinforced toetip area</u> : declared brown testa di moro color TPU (PU003TM); <u>upper</u> : brown water-repellent leather (PEI/MAR), coupled with white felt; <u>collar</u> : brown testa di moro color fabric coupled with "PE40" (TLA/TMO); <u>tongue/bellows</u> : brown testa di moro color fabric "TECNIC L." (TEL/TMO), lined and centrally padded; <u>vamp and quarter lining</u> : black three-dimensional fabric (SPO/SELN), that covers also the insole; <u>collar and tongue lining</u> : brown "6009" color three-dimensional fabric (A8S/6009); <u>insole</u> : beige non-woven fabric "Strong Antistatico lbitech" declared thickness 2,5 mm (ST2/GRI); <u>penetration resistant insert</u> : recycled isolating composite material, art. "Ibisafe D31-036- IS1" mm4 black stamp marked "BIAGIOLI Ibisafe EN12568:2010 CSA Z195:2002, suitable ISO 20344:11" (LC/IB31); <u>removable insock</u> : black antistatic material "Arnetech XMAX nero + rubber verde + tessuto moncayo pet black + memory canario al centro" (F0008A); <u>toecap</u> : aluminium, art. "522/S SHELL" (522SALL).		
Tec <mark>hnical Sta</mark> ndard:	EN ISO 20344:2011 (UNI EN ISO 20344:2012)Personal protective equipment – Test methods for footwearEN ISO 20345:2011 (UNI EN ISO 20345:2012)Personal protective equipment – Safety footwear		
Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.		
Size range:	from 36 to 48		
Technical File:	DC-14967/E		
Test report:	RCT nº4131617/E		



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





## EU Type Examination Certificate

Date: 2022/05/20	n. 769222001/OE	Validity: 2027/05/19
Functions and performance levels:	basic requirements for safety footwear (see Table mandatory ones, among which:	2 and 3 of EN ISO 20345:2011): all
	SRC (*) = Slip resistance – meets the following require - <u>surface</u> : ceramic / <u>lubricant</u> : detergent solution; - <u>surface</u> : steel / <u>lubricant</u> : glycerol.	ement:
	(*) the final level of the anti-slip features is achieved after t	he first hours of trial stage.
	Additional requirements (Tab. 18 and 20 of EN ISO 20 S3 = closed seat region, antistatic properties, resistance to fuel oil, water penetration resistance upper), penetration resistance, cleated outsole; HR outsole; HI = heat insulation of sole complex; CI = co WR = resistance to water penetration of the whole for Note: the penetration resistance of the synthetic stitch diameter of the perforating object; in return the synthetic ergonomics advantages (flexibility, insulation, humidity and	energy absorption of seat region, ce and absorption (water-repellent O = resistance to hot contact of the old insulation of the sole complex; potwear. proof insole tends to decrease with the insole offers more protective surface and
	<ul> <li>CE Marking;</li> <li>Name/Trademark and complete address of the M</li> <li>designation of the footwear (= alphanumeric cod</li> <li>nr. and year of the Standard of reference + safety</li> <li>size of the footwear;</li> <li>production date (month + year);</li> <li>additional information: internal codes.</li> </ul>	le: unique/unambiguous);
CA CE EN IS 02:/ S3 HRO 21434 705	F10artt C.         F705159.201         S020345:2011         2022         HI CI WR SRC         813925         159c1t         42         HARTT BV	

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

