

CD-2 COMPANY 625 WILLOWBROOK CTR PKWY WILLOWBROOK, IL 60527

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier Product Name: Product Code (SKU):

CD-2 Oil Stop Leak 4105R (50002)

1.2 Relevant Identified Uses Of The SubstanceProduct Use:Engine Oil Additive – Seal Swell Stop Leak

1.3 Details of the Supplier of the SDS

Company Name: Street Address: City, State, Zip Code: CD-2 Company 625 Willowbrook Centre Parkway Willowbrook, Illinois 60527

1.4 Emergency Telephone Numbers

Phone Number:	1(630)455-3700
Fax Number:	1(630)455-3868
Transportation:	1(800)424-9300 (CHEMTREC)
Medical Assistance:	Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: Skin irritation 3 Aspiration toxicity 2

2.2 Label Elements



Warning

Pictogram:

Signal Word:

Hazard Statement:

May be fatal if swallowed and enters airways.

Precautionary Statement: Wear shield read a

Wear protective gloves, clothing, eye glasses and face shield. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. If exposed, get medical attention. If on skin or hair, remove immediately all contaminated clothing and launder before re-use. Wash skin with soap and water. If skin irritation occurs, get medical attention. If swallowed, immediately call a poison control center or doctor. Do NOT induce vomiting. Store in a well ventilated place. Dispose of contents and container in accordance with all local, state, national and international regulations.

2.3 Other Hazards

Description of additional HNOC: None

3. Information on Ingredients:

pplicable
Number Concentration (wt%)
2-58-1 <u>60-90%</u>
2-62-7 20-30%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist or you feel un-well.

Skin: In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and footwear. Launder clothing before re-use. Call a physician if irritation develops or persists.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a poison control center or physician.

4.2 Most important symptoms and effects – acute and chronic

Inhalation:	May cause respiratory tract irritation. Vapors may cause drowsiness or dizziness.
Skin:	May cause skin irritation. Symptoms may include redness, drying, defatting, and dermatitis.
Eyes:	May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.
Ingestion:	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects develop or persist and you feel un-well.

5. Fire Fighting Measures:

5.1 Extinguishing media

Carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water. See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate all source of ignition.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Do not flush to sewer or allow to enter waterways. See section 8 for PPE.

For clean up: Take up material and place in a suitable container. Vapors may be heavier than air and may travel along the ground to a distant source of ignition. Provide adequate ventilation.

7. <u>Handling and Storage</u>

7.1 Precautions for safe handling

Keep away from source of ignition. Do not smoke. Take precaution to eliminate static discharge. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. Do not eat or drink while handling. Wash hands with soap and water after handling. Use only non-sparking tools.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored.

8. Exposure Control/Personal Protection:

8.1 Control parameters

Exposure Limits 8 hr TWA:	(OSHA PEL)	<u>(ACGIH TWA)</u>
Petroleum Distillates (Hydrotreated Spent	5 mg/M ³ oil mist	5 mg/M ³ oil mist
Lube Oil)		
Residual Oils, Petroleum, Solvent Dewaxed	d 5 mg/M³ oil mist	5 mg/M ³ oil mist

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves to prevent skin contact.Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form: viscous liquid Color: clear yellow Odor: typical oily Odor Threshold: not available pH: not available pH: not available pH: ot available pH: ot available pH: s260°C (>500°F) Flash Point (Seta Closed Cup): >93°C (>500°F) Flash ability Limits: Explosive Limits: Evaporation Rate: not available Ivamability Solid/Gas: not applicable Vapor Pressure: not available Vapor Pressure: not available Vapor Pressure: not available Vapor Density: not available Vapor Pressure: not available Vapor Pressure: not available Vapor Density: not available Vapor Pressure: not available Vapor Pressure: not available Vapor Pressure: not available Vapor Pressure: not available Vapor Density: not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt	9.1 Information of basic chemical and physical properties		
Evaporation Rate: not available Flammability Solid/Gas: not available Vapor Pressure: not available Vapor Density: not available Specific Gravity: 0.872 Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9.2 Other information 0.0% % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials 10.5 Incompatible materials 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons	Color: Odor: Odor Threshold: pH: Melting Point/Freeze Point: Initial Boiling Point: Flash Point (Seta Closed Cup):	clear yellow typical oily not available not applicable – oil based product -6°C (21°F) >260°C (>500°F) >93°C (>200°F)	
Flammability Solid/Gas: not applicable Vapor Pressure: not available Vapor Density: not available Specific Gravity: 0.872 Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9.2 Other information 0.0% % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO2, CO and hydrocarbons Co2, CO and hydrocarbons			
Vapor Pressure: not available Vapor Density: not available Specific Gravity: 0.872 Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9. 2 Other information 5.0 – 6.0 cSt % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 10.0% Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO2, CO and hydrocarbons Co2, CO and hydrocarbons	•		
Vapor Density: not available Specific Gravity: 0.872 Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9. 2 Other information 00% % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity 0.0% Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products GO2, CO and hydrocarbons CO2, CO and hydrocarbons		• •	
Specific Gravity: 0.872 Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 - 6.0 cSt 9. 2 Other information 5.0 - 6.0 cSt % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons			
Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9. 2 Other information 5.0 – 6.0 cSt % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity 0.0% Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Storig oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO2, CO and hydrocarbons CO2, CO and hydrocarbons			
Partition coefficient (n/octonol/water): not available Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9. 2 Other information 100% % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity 0.0% Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons			
Viscosity (Kinematic @ 100°C): 5.0 – 6.0 cSt 9. 2 Other information % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons			
9. 2 Other information % NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons	· · · · · ·		
% NVM by Weight: 100% % VOC Content (California): 0.0% 10. Stability and Reactivity: 0.0% 10. Stability and Reactivity: 0.0% 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons	VISCOSITY (KINEMATIC @ 100°C):	5.0 - 6.0 CST	
% VOC Content (California): 0.0% 10. Stability and Reactivity: 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons CO	9.2 Other information		
 10.1 Reactivity Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO₂, CO and hydrocarbons			
Does not react under normal conditions 10.2 Chemical stability Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons	10. Stability and Reactivity:		
 Stable 10.3 Possibility of hazardous reactions Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO₂, CO and hydrocarbons 	•		
Does not react under normal conditions 10.4 Conditions to avoid Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons			
 Heat and incompatible materials 10.5 Incompatible materials Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO₂, CO and hydrocarbons 	•	; ;	
Strong oxidizers such as bleach and peroxides 10.6 Hazardous decomposition products CO ₂ , CO and hydrocarbons			
CO ₂ , CO and hydrocarbons	•		
11. Toxicological Information:		ts	
	11. Toxicological Information:		

11.1 Information on Toxicological effects

Petroleum Distillates Hydrotreated Spent Lube Oil (64742-58-1)

LD50 – Oral Rat	>5000 mg/Kg
LD50 – Dermal Rabbit	>5000 mg/Kg
LC50 – Inhalation Rat	>5 mg/L (4 hr)

Residual Oils, Petroleum, Solvent, Dewaxed (64742-62-7)

LD50 – Oral Rat	>5000 mg/Kg
LD50 – Dermal Rabbit	>5000 mg/Kg
LC50 – Inhalation Rat	>5 mg/L (4 hr)

Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organs – single expos	May cause skin irritation Based on available data, classification data are not met Based on available data, classification data are not met
Opeenie larget organis Single expe	Based on available data, classification data are not met
Specific torget organs repeated av	•
Specific target organs – repeated ex	
Aspiration hazard	Based on available data, classification data are not met May be fatal if swallowed and enters air ways.
Symptoms/injuries after inhalation	May cause respiratory tract irritation.
Symptoms/injuries after skin contact	May cause skin irritation. Symptoms may include redness, drying, defatting, and dermatitis.
Symptoms/injuries after eye contact	May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects None known

13. Disposal Considerations:

13.1 Waste treatment methods

RCRA Hazardous Waste:	Not regulated as a hazardous waste.
Waste Disposal Method:	Dispose of in accordance with local, state and federal
	regulations
Waste Disposal Vessel:	Metal drums are recommended.

14. Transportation Information:

14.1 UN number Not Regulated

14.2 UN Proper shipping name None

14.3 Transport Hazard class None

14.4 Packaging group None

14.5 Marine Pollutant No

14.6 Transportation in Bulk Not applicable

14.7 Special precautions None

15. Regulatory Information:

15.1 US Federal Regulations

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

15.3 State Regulations

State Regulatory Information:

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

CAS Number	Concentration		State Code
None			
15.4 HIMS & NFPA Cla	ssifications		
HIMS Classification:	Health	1	
	Flammability	1	
	Reactivity	0	

NFPA Classification:	Health	1
	Flammability	1
	Reactivity	0

16. Other Information:

Reason For Issue	Conversion to OSHA GHS SDS Format
Prepared By	James Heidel
Preparer's Title	Technical Director, R&D
SDS Administrator	Jean Mayszak - Technical Compliance Manager, R&D
Approval Date	March 10, 2015
Supersedes Date	September 1, 2013
Revision Number	#7

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitableness and completeness of such information for their own particular use.