

Product Information

5-Digit	10-Digit	Test Voltage	Pre-heating Time (in seconds)	Male Thread (D1)	SW (mm)	Tightening Torque (Nm)	L1 +/- 0.5 mm	L2 +/- 0.5 mm	D2 (mm)	D3 (mm)	Conical Seat @ Degrees
80003	0250001016	0.9	<20	M18 x 1.5	21	20-30	89	28	M5	10	60
80006	0250201039	11.0	4	M12 x 1.25	12	15-25	71	25	M5	6	63
80010	0250201032	11.0	4	M12 x 1.25	12	15-25	59	21	M5	6	63
80011	0250201035	11.5	4	M12 x 1.25	12	15-25	120	28	Plug	6	63
80012	0250201036	11.0	4	M12 x 1.25	12	15-25	76	21	Plug	6	63
80013	0250201038	11.0	4	M12 x 1.25	12	15-25	116	28	Plug	6	63
80014	0250202005	11.0	<8	M10 x 1.0	12	10-15	89	25	M4	5	119
80015	0250202007	7.0	<16	M10 x 1.25	12	15-20	84	23	M4	5	119
80016	0250202008	5.0	<19	M10 x 1.25	12	15-20	90	24	M4	5	119
80017	0250202013	6.5	<20	M12 x 1.25	12	20-25	61	20	M5	6	63
80018	0250202051	7.0	<20	M10 x 1.25	12	15-20	101	28	M4	5	93
80019	0250202054	7.0	<20	M10 x 1.25	12	15-20	95	31	M4	5	93
80020	0250202089	11.0	4	M10 x 1.25	12	15-20	86	22	M4	5	120
80021	0250202073	6.0	<12	M10 x 1.25	12	15-20	95	31	M4	5	93
80024	0250202251	6.0	<10	M10 x 1.0	10	10-15	79	27	Blade	5	93
80027	0250202254	6.0	<10	M10 x 1.0	10	15-20	81	27	Plug	5	93
80028	0250202022	11.0	4	M10 x 1.0	10	10-15	92	25	M4	5	63
80031	0250201041	11.0	4	M12 x 1.25	12	15-25	69	23	M5	6	63
80033	0250202127	11.0	4	M10 x 1.0	10	10-15	130	31.5	Plug	5	93
80034	0250202126	11.0	4	M10 X 1.0	10	10-15	80	28	Blade	5	93
80035	0250201044	11.0	4	M18 x 1.5	21	20-30	75	29	M5	6	63
80036	0250202045	11.5	4	M10 X 1.0	10	19	130	28	Plug	5	63
80037	0250202133	11.0	4	M14 x 1.25	14	20-35	122	24	Pin	5	123
80038	0250202134	11.0	4	M10 x 1.25	10	10-15	136.5	28.4	M4	3.4	123
80039	0250202023	11.0	4	M10 x 1.0	10	10-15	97.2	30	Pin	5	63
80042	0250203010	4.7	4	M10 x 1.0	12	15-25	136.5	28	M4	3	123
80043	0250212007	11.0	4	M14 x 1.25	10	20-35	120	21.4	Pin	5	121
80044	0250203011	4.7	4	M10 x 1.0	12	15-25	137	28	M4	3	123
80045	0250603009	7.0	<2	M10 x 1.0	10	10-15	106	33	Pin	3.2	63
80046	0250403007	4.4	3	M10 x 1.0	10	10-15	130	28	Pin	3.3	63
80049	0250212008	11.0	4	M14 x 1.25	10	20-5	121	21.4	Pin	5	121
80050	0250403008	4.4	3	M8 x 1.0	8	10-15	149	27	Pin	3.3	93

sw = width across flats

