

DEIONIZED WATER

MULTI-PURPOSE



HELPS TO DECREASE THE MAINTENANCE REQUIREMENTS OF ENGINE RADIATORS AND LEAD-ACID BATTERIES, BY REDUCING THE DAMAGING EFFECTS OF SCALE BUILD-UP AND CORROSION CAUSED BY THE USE OF REGULAR TAP WATER.



FOR USAGE IN ENGINE RADIATORS



HELPS PREVENT SCALE BUILD UP AND REDUCE CORROSION IN THE ENGINE COOLING SYSTEM



LOW ELECTRICAL CONDUCTIVITY



IMPROVES PERFORMANCE OF VEHICLE BATTERY COMPARED TO REGULAR TAP WATER

AUTOMOTIVE STANDARDS	MEETS ASTM D3306 (FOR COOLANT USAGE)
FLAMMABLE	NO
FREEZING POINT	0°C (32°F)
BOILING POINT	100°C (212°F)
TOXICITY	NONE
PRIMARY COLOUR	CLEAR
рH	5.5 TO 8.5







TURBO POWER™ DEIONIZED WATER IS AVAILABLE IN 3.78L, DRUMS & TOTES

PRODUCT SPECIFICATIONS

ITEM #	UNIT/CASE PACK	UPC	SCC14
15-034	4 X 3.78 L	056438150343	40056438150341
25-039	1 X 208 L	056438910442	-
25-039-275	1 X 1041 L	056438910459	-

