

TECTRAN HOSE END REPAIR KITS

FOR DOT TYPE A SAE J1402 1/2" ID HOSE WITH MIN. OD OF 7/8"

Tectran's field install repair kit is a permanent solution for damaged 1/2" I.D. air brake hoses. Our 3/8" NPT Live Swivel enables a quick fix in any environment without the need to detach both ends.


EASY INSTALLATION IN 3 QUICK STEPS

1



Twist sleeve clockwise onto hose until the internal face of the sleeve seats against hose end.

2



Insert barb fitting end into hose opening. Use a wrench to hold sleeve in place while you turn barb fitting clockwise using hex key. Stop tightening when the nut on barb fitting no longer turns.

3



Use hex key to turn fitting counter-clockwise by 1/4 turn. The nut on the barb fitting should rotate easily in either direction. Conduct a quick pull test on the hose and fitting to ensure that the hose is firmly gripped inside.



- Brass construction of sleeve & barb for corrosion protection
- Package contains two repair fittings for 1/2" I.D. Rubber air brake hoses
- 3/8" NPT Live Swivel allows the hose to move freely while in service
- Dual O-ring design for added leak protection
- Installable with only an adjustable wrench and the included hex key
- Meets or exceeds SAE J1402 - Type A



(A) HOSE
RETAINING
SLEEVE



(B) BARB
FITTING



(C) 5/16"
HEX KEY

*REQUIRED TOOL: ADJUSTABLE WRENCH

Kit No. 70-31802
Stk. Code: 23854
(Contains: 2 x 3/8" NPT Swivel Ends)



| Part No. | Stk. Code | Thread | Pack Size |
|----------|-----------|--------|-----------|
| 70-31802 | 23854 | 3/8" | 2 |
| 70-31806 | 23925 | 3/8" | 5 |
| 70-31804 | 23924 | 3/8" | 10 |

For Complete Tectran Patent & Trademark information, see www.tectran.com/patents



TECTRAN - USA
2345 Walden Ave., Suite 100
Cheektowaga, NY 14225

Ph: 800.776.5549
Fx: 716.894.9623
E: orders@tectran.com

TECTRAN - CANADA
2881 Brighton Road
Oakville, ON L6H 6C9

Ph: 905.678.7700
Fx: 905.678.6210
E: customerservice@tectran.com

www.tectran.com

Stock # PB20192202
©2019 Tectran
All Rights Reserved.