SAFETY DATA SHEET



1. Identification

Product identifier NAPA XL Boddyfiller hardener

Other means of identification

Product Code 765-1244 Hardener

Recommended use Cream Hardener, Polymer Reaction Catalyst

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Balkamp, Inc.

Address 2601 South Holt Road

Indianapolis, Indiana 46241

United States

Telephone Information 1-800-468-6832

E-mail msds@balkamp.com
Contact person Stephanie Pruitt

Emergency phone number Emergency 1-317-244-7241

2. Hazard(s) identification

Physical hazards Organic peroxides Type E

Health hazards Serious eye damage/eye irritation Category 2B

Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Heating may cause a fire. May cause an allergic skin reaction. Causes eye irritation. Very toxic to

aquatic life.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep/Store away from

clothing and other combustible materials. Keep only in original container. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/eye protection/face protection.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Wash

contaminated clothing before reuse. Collect spillage.

Storage Protect from sunlight. Store at temperatures not exceeding 25°C / 77°F. Keep cool. Store away

from other materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 27.95% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment.

3. Composition/information on ingredients

Mixtures

Material name: NAPA XL Boddyfiller hardener

Chemical name	Common name and synonyms	CAS number	%	
Benzoyl peroxide		94-36-0	50 to <60	
Zinc Stearate		557-05-1	5 to <10	
Calcium Sulfate Dihydrate		7778-18-9	1 to <5	
iron oxide		1309-37-1	0.1 to <1	
Other components below reportable	levels		30 to <40	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

Ingestion

delayed

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Heating may cause a fire.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

765-1244 Hardener Version #: 01 Issue date: 12-18-2015

Material name: NAPA XL Boddyfiller hardener

SDS US

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from heat, sparks and open flame. When using do not smoke. Keep away from clothing and other combustible materials. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Keep only in the original container. Store away from other materials.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Benzoyl peroxide (CAS 94-36-0)	PEL	5 mg/m3	
Calcium Sulfate Dihydrate (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
iron oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Zinc Stearate (CAS 557-05-1)	PEL	5 mg/m3	Respirable fraction.
•		15 mg/m3	Total dust.
US. ACGIH Threshold Limit			F
Components	Туре	Value	Form
Benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Calcium Sulfate Dihydrate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Zinc Stearate (CAS 557-05-1)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Calcium Sulfate Dihydrate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Zinc Stearate (CAS 557-05-1)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
ogical limit values	No biological exposure limits noted to	for the ingredient(s).	
osure guidelines	Occupational Exposure Limits are no	ot relevant to the current physic	al form of the product.
propriate engineering trols	Good general ventilation (typically 1 should be matched to conditions. If a or other engineering controls to main exposure limits have not been estable eyewash station.	applicable, use process enclosu ntain airborne levels below reco	res, local exhaust ventilation, mmended exposure limits. If
vidual protection measures,	such as personal protective equipr	nent	
Eye/face protection	Wear safety glasses with side shield	ls (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant		

Material name: NAPA XL Boddyfiller hardener

Other

Respiratory protection

SDS US

supplier.

Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid.

Solid. Paste Paste. **Form**

Color Red

Odor Not available. Not available. **Odor threshold** Not available. рH Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

0.0002 hPa estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature**

122 °F (50 °C) SADT **Decomposition temperature**

Viscosity Not available.

Other information

Density 9.98 lbs/gal **Explosive properties** Not explosive. Oxidizing properties Not oxidizing 20 % estimated Percent volatile

Specific gravity 12

VOC 20 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Hazardous polymerization does not occur. Possibility of hazardous

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Sunlight. Avoid temperatures

exceeding the decomposition temperature. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Combustible material. Amines. Alcohols. Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation

Skin contact May cause an allergic skin reaction.

Causes eye irritation. Eve contact

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May

cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components **Species Test Results**

Benzoyl peroxide (CAS 94-36-0)

Acute

Oral

LD50 Rat 7710 mg/kg

* Estimates for product may be based on additional component data not shown.

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzoyl peroxide (CAS 94-36-0) 3 Not classifiable as to carcinogenicity to humans. iron oxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

12. Ecological information

Ecotoxicity Very toxic to aquatic life.

Components **Test Results Species**

Calcium Sulfate Dihydrate (CAS 7778-18-9)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Material name: NAPA XL Boddyfiller hardener

765-1244 Hardener Version #: 01 Issue date: 12-18-2015

Partition coefficient n-octanol / water (log Kow)

3.46 Benzoyl peroxide

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number **UN3108**

UN proper shipping name ORGANIC PEROXIDE TYPE E, SOLID (<52% Dibenzoyl Peroxide as a paste), MARINE

POLLUTANT (Benzoyl peroxide)

Transport hazard class(es)

5.2 Class Subsidiary risk Label(s) 5.2

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number

Organic peroxide type E, solid (<52% Dibenzoyl Peroxide as a paste) **UN proper shipping name**

Transport hazard class(es)

Class 5.2 Subsidiary risk

Not applicable. Packing group

Environmental hazards No. **ERG Code** 5L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

UN number **UN3108**

ORGANIC PEROXIDE TYPE E, SOLID (<52% Dibenzoyl Peroxide as a paste), MARINE UN proper shipping name

POLLUTANT

Transport hazard class(es)

Class 5.2 Subsidiary risk

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes F-J.S-R **FmS**

765-1244 Hardener Version #: 01 Issue date: 12-18-2015

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

DOT; IATA



IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, $29\ CFR\ 1910.1200$.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc Stearate (CAS 557-05-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Benzoyl peroxide	94-36-0	50 to <60	
Zinc Stearate	557-05-1	5 to <10	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Benzoyl peroxide (CAS 94-36-0)

Calcium Sulfate Dihydrate (CAS 7778-18-9)

iron oxide (CAS 1309-37-1) Zinc Stearate (CAS 557-05-1)

US. New Jersey Worker and Community Right-to-Know Act

Benzoyl peroxide (CAS 94-36-0)

Calcium Sulfate Dihydrate (CAS 7778-18-9)

iron oxide (CAS 1309-37-1) Zinc Stearate (CAS 557-05-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzovl peroxide (CAS 94-36-0)

Calcium Sulfate Dihydrate (CAS 7778-18-9)

iron oxide (CAS 1309-37-1) Zinc Stearate (CAS 557-05-1)

US. Rhode Island RTK

Benzoyl peroxide (CAS 94-36-0) Zinc Stearate (CAS 557-05-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

C.I. Pigment Yellow 13 (CAS 5102-83-0) Listed: October 1, 1992

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 12-18-2015

Version # 01

765-1244 Hardener Version #: 01 Issue date: 12-18-2015

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 2 Personal protection: D

NFPA ratings Health: 2

Flammability: 0 Instability: 2

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Material name: NAPA XL Boddyfiller hardener

765-1244 Hardener Version #: 01 Issue date: 12-18-2015 9 /