

Specifications

HPFi

Hannah 832 Bariatric Patient Treatment Chair with Trendelenburg

Frame

- Seat, back and arms are engineered hardwood
- Components are glued and nailed
- Reinforcing corner blocks are glued and stapled

Suspensions

- Seat suspension built with heavy-duty, 8-gauge sinuous wire springs running front-to-back and secured to the frame at either end. Two tie-wires stretch left-to-right behind springs and are metal-fastened to each spring, creating a single, cohesively strong seat suspension system.
- Seat suspension is fiber-covered to prevent metal springs from contacting foam.
- Back is 100% Sytex sheet webbing and passes the following fire ratings:
 - UFAC - Class 1
 - NFPA 260A - Class 1
 - CAL 117-2013
 - FNE 83-258B

Functions

- 750 lb. weight capacity and extra wide seat
- Lay-flat mechanism allows for a variety of treatments
- Trendelenburg allows a 3° negative pitch when reclined fully
- Pneumatically controlled back with infinite adjustments operated by finger pull located on outside of right arm facing
- Full length foot rest operated by lever on side of chair provides support for entire leg
- Pull-out foot tray for easy patient transfer
- Four swivel casters (locking on rear) offer zero-turning radius for maneuverability

Foam

- CFC-free, Bio-Flex™ Hybrid includes soy-based foam
- Seat: 4.5" thick 2.5 Density 55 UC
- Back: Molded Contoured Cut Foam 1.4 Density 27 CFR
- Footrest (Part 1= .75" thick & Part 2= .5" thick) 1.5 Density, 45 CFR
- CAL 117-2013 rated (CFR)

Upholstery

- Standard fabrics tested for high wear (most more than 30,000 double rubs Wyzenbeek Wire Mesh test).
- See individual upholstery specification sheet(s) for details regarding stain resistance, anti-microbial, moisture resistance, etc.
- Available in textile or coated fabric upholstery in a single or two-tone



Dimensions

- Overall: 37"W x 39"D x 46"H
- Recline depth: 73" Reclined flat
- Seat: 28.5"W x 20"D x 20"H
- Back: 28"W x 29"H
- Arm Height from Seat: 9"

Warranty

- Limited Lifetime on seating components.
- Three years on mechanism
- Meets or exceeds applicable industry test standards

Ships

- With back detached, easy attachment
- Weight: 238 lbs.
- Cu. ft.: 45
- Via truck
- Freight class: 150

Environmental & Sustainability Materials & Resources



Standard material use in products in accordance with the following standards:

- LEED for Commercial Interiors EA Credit, 50% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, 75% Construction Waste Diversion (1 point)
- LEED for Commercial Interiors EA Credit, Resource Reuse 30%, Furniture & Furnishings (1point)
 - HPFi Lifetime warranty and Second Life program applicable for reuse
- LEED for Commercial Interiors MR Credit, Regional Materials 20% (1 point) - HPFi products are manufactured in High Point, NC and may contribute this point based on project location.