

800-558-1010 www.NBF.com

> 532 lbs (avg. ship wt.) 31 15/16" FILING WIDTH 10 3/8" 27 3/4" **FILING CHASSIS HEIGHT HEIGHT** 37 1/2" **CHASSIS WIDTH**

MODEL 2-3822-C:

907 lbs (avg. ship wt.) 31 15/16" FILING WIDTH 10 3/8" **FILING HEIGHT** 52 3/4" CHASSIS **HEIGHT**

37 1/2"

CHASSIS WIDTH

15 11/16"

FILING

DEPTH -

SIDE VIEW:

43 1/4" OVERALL WITH

- DRAWER EXTENDED

22 1/8"


CHASSIS -

MODEL 4-3822-C:

Filing Arrangements:




SIDE TO SIDE



ADAPTER HANGER (OPTIONAL)

LETTER FILING



FIREPROOF INSULATION is 100% gypsum, reinforced by a 1" by 2" lattice made of 14-gauge galvanized welded steel wire, providing complete peace of mind from fire, impact, or explosion.

FIELD REPLACEABLE STEEL PANELS can easily be replaced in the event that any panel is damaged.

FINISH is an environmentally-friendly electrostatic powder coating applied to all sides, including bottom. The finish is scratch-resistant, providing a lifetime quality appearance. Standard colors available include: parchment, tan, taupe, brown, black, sand, champagne, platinum, and pewter.

DRAWER BODIES are built with high sides for use with hanging folders – no additional frames are needed. *Each file includes 2 cross hanger per drawer. **DRAWER SUSPENSIONS** are maintenance free.

DRAWER LOCKS are 4-pin key locks.

DRAWER PULLS are recessed for best space utilization.

INSULATION BETWEEN ALL DRAWERS makes each drawer a separate insulated container.

WATER RESISTANCE means files are designed to prevent water damage resulting from sprinklers and

Dimensions

 $\pm \frac{1}{16}$ inch

2-POSITION DRAWER CATCH allows access to certain drawers while others remain locked.

INTERLOCKS prevent more than one drawer from opening at the same time to protect users from accidental tipping.

DRAWER HEADS are formed of welded steel and filled with fireproof insulation, and are field replace-

UNDERWRITERS LABORATORIES" (UL") FIRE & IMPACT RATING on all file cabinets. These models carry the 1-Hour Class 350 Fire with Impact UL label. Tests include 1 hour exterior fire exposure at 1700°F, a 2000°F explosion test, and a 30 foot drop to test integrity.

OPTIONAL UPGRADES are available to enhance your file's appearance or functionality. Upgrades available include custom color finishes, standard lock options, casters, and interior options such as adapter hangers, document inserts, trays, cross hangers, and inner drawers.

DURAVAAULT'S LIMITED LIFETIME WARRANTY on all mechanical or operable parts. Associated labor costs will be paid by our manufacturer for two years from the date of purchase. If your DuraVault file sustains any damage while protecting documents from a fire, our manufacturer will replace the file free of charge. DuraVAult is manufactured under agreement with FireKing. For more details and warranty registration please visit www.fireking.com.









Customer Service Hotline 800-626-6060 WWW.NBF.COM