Model ESS-100-BLK Mesh and Fabric Chair (Black)

Parts Listing

A Chair Back 1 Unit

B Chair Seat 1 Unit



C Chair Arms 2 Units


Seat Mechanism
1 Unit





E Gas Lift 1 Unit

Chair Base



G Casters 5 Units

Screws (1/4" x 3/4") 4 Units



I J Screws (1/4" x 1") Screws (1/4" x 1-1/4") 4 Units 6 Units



K

Washers 6 Units









Assembly Instructions


STOP


Tools Needed: Allen Wrench - Supplied Please read all instructions before assembly.


- Step 1: Insert Casters (G) into Chair Base (F). Insert Gas Lift (E) into Chair Base (F).
- Step 2: Attach Chair Arms (C) to Chair Back (A) using Screws (I). Tighten with Allen Wrench (L).
- Step 3: Attach Chair Arms (C) to Chair Seat (B) using Screws (J) and Washers (K). Tighten with Allen Wrench (L).
- Step 4: Attach Seat Mechanism (D) to bottom of Chair Seat (B) using Screws (H). Tighten with Allen Wrench (L).
- **Step 5:** Take entire chair frame and place the hole in the center of the Seat Mechanism (D) onto Gas Lift (E). Press down firmly to secure.
- Step 6: Now your chair is fully assembled.














WEIGHT CAPACITY: 250 lbs.

Assembly Notes:

During assembly, hand tighten screws only. When all screws are in place, you may then tighten all screws completely.

CAUTION:

- 1. Do not use this chair as a step ladder.
- 2. Check for loose screws and tighten them every 6 months.

