

BEHR DYNASTY® Interior Eggshell Enamel



- Advanced Stain Repellency
- One-Coat Hide Guaranteed[†]
- Scuff & Mar Resistant
- Fast Drying - Doors Won't Stick After 4 hrs. [△]
- Ideal for High - Traffic Areas

- Stain-Blocking Paint & Primer[‡]
- Exceptional Washability & Durability
- Lifetime Limited Warranty*
- Low VOC, 100% Acrylic
- Antimicrobial-Mildew Resistant Paint Finish

No. 2650 ULTRA PURE WHITE®
No. 2653 Deep Base
No. 2654 Medium Base



[‡]A primer coat may be needed on some surfaces. See preparation and prime for details.



1 Hr Dry Time
2 Hr Recoat Time



Up to 400 Sq. Ft.
Coverage per Gallon



Soap & Water
Clean-Up



Protect
from Freezing

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

BEHR DYNASTY®

Stain-Blocking Paint & Primer is our best interior paint providing stain repellency, exceptional durability, plus an Exclusive BEHR DYNASTY & MARQUEE® One-Coat Color Collection.

[†]Guaranteed one-coat coverage excludes ULTRA PURE WHITE® and colors outside of the BEHR DYNASTY & MARQUEE® Interior One-Coat Color Collection. Multiple coats are required in the following situations: 1) Painting over uncoated, porous, or repaired surfaces; 2) Over woods that contain tannins such as redwood or cedar; or 3) When painting over heavy stains, which may require spot priming, multiple coats and/or longer dry time.

WHERE TO USE

Ideal for every room and delivers a durable velvety appearance.

PREPARATION & PRIME

Properly prepare and clean all surfaces. Remove loose paint, wash off dirt and grease with detergent, rinse and allow to dry. Remove mildew stains with a mildew stain remover. Scuff sand glossy surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. Allow new stucco, plaster and masonry to cure for 30 days before painting. Use DYNASTY Paint as a primer for uncoated, porous or repaired interior surfaces, including woods that contain tannins (two primer coats required for redwood and cedar). **STAINED SURFACES:** Lock in stains with DYNASTY Paint as a spot primer. For heavy stains, test for stain bleed-through by applying DYNASTY Paint to a small section. If the stain bleeds through, spot prime with another coat to the stained area and test again before topcoating. If bleeding continues, a longer dry time is needed before topcoating.

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to the original residential consumer purchaser the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified upon inspection by our representative during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Paint Company Representative, call 1-800-854-0133 Ext. 2 (U.S.A. only).

APPLICATION

Apply when air and surface temperatures are between 50 – 90°F (10 – 32°C). Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. Use a high quality 3/8 – 1/2" nap roller cover, nylon/ polyester brush or an airless sprayer (.015 – .019" spray tip, 60 mesh filter). Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. Fully saturate roller for best coverage.

[△] Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.

After 1 week, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. The dry paint film is mildew resistant. **Do not use on floors.**

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS: ETHYLHEXYL BENZOATE, CRYSTALLINE SILICA AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



©2023 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 2/23