



BEHR MARQUEE® Exterior Flat

- Exceptional Resistance to Dirt & Fading
- One Coat Coverage in 700+ colors*
- Advanced Stain-Blocking Paint & Primer^o
- Advanced Technology for Longer Lasting Color

^oA primer coat may be needed on some surfaces. See preparation and prime for details.

- Resists Rain Shortly After Application
- Low Temperature Application
- Antimicrobial-Mildew Resistant Paint Finish
- Lifetime Limited Warranty*
- Low VOC, 100% Acrylic

No. 4450 Ultra Pure White®

No. 4453 Deep Base**

No. 4454 Medium Base



1 Hr Dry Time
2 Hr Recoat Time



250 – 400 Sq. Ft.
Coverage per Gallon



Soap & Water
Clean-Up



Protect
from Freezing

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

BEHR MARQUEE®

BEHR MARQUEE® Stain-Blocking Paint & Primer delivers remarkable dirt and fade resistance for the exterior of your home. Tintable to over 700+ One Coat Hide Colors. Your home will look freshly painted longer, even under the most challenging weather conditions.

WHERE TO USE

For use on properly prepared Wood, Vinyl, Aluminum, Fiber Cement Siding, Metals, Steel, Brick, Masonry, Stucco and Fences.

PREPARATION & PRIME

Use on properly prepared and cleaned coated and uncoated Exterior surfaces. Countersink nailheads, fill and sand smooth. Remove rust, loose or peeling paint. Repair imperfections and sand smooth. Wash off dirt, grease and chalk with detergent and/or powerwash. Remove mildew stains with a mildew stain removing product. Clean and sand new or weathered wood. Scuff sand or degloss smooth or glossy surfaces. Scuff sand or etch metals. Rinse and allow to dry. Caulk windows, doors and other openings. Allow new stucco, plaster and masonry to cure for 30 days before painting. Use MARQUEE Paint as a primer for repaired or uncoated surfaces, including woods that contain tannins and heavily stained areas (two primer coats required for redwood and cedar). Lock in stains with the first primer coat; if necessary, apply a second primer coat of MARQUEE Paint. For drastic color changes or when applying deep colors denoted with a dagger (†) on the color chip, apply a tinted primer coat of MARQUEE Paint, if needed.

APPLICATION

Apply product on dry substrates when air and surface temperatures are between 35°-90° F (2° – 32° C) and will remain between 35° – 90° F (2° – 32° C) for at least 4 hours after applying. Allow paint film to dry for at least 60 minutes prior to rain showers when temperatures are between 60° – 70° F (15° – 21° C) and 60 – 70% relative humidity.

Lower temperatures, higher humidity or deep colors may increase dry time and/or rain resistance time. Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. On semi-smooth surfaces, use a high quality 3/8 – 1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 – .021" spray tip, 60 mesh filter). On rough surfaces, use a high quality 3/4 – 1" nap roller cover. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. On heavy stains and woods that contain tannins, allow 12 – 16 hours of dry time between coats. After 4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant. When applying to vinyl, color choice must be the same color or lighter than the existing color. Do not use on floors.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to the original residential consumer purchaser the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified upon inspection by our representative during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Coatings Professional, call 1-800-854-0133 Ext. 2

©2020 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 02/21
** 3 Hr Recoat Time for Deep Base only



*For details visit behr.com/marquee-guarantee

⚠ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS DIURON, ETHYLHEXYL BENZOATE, CRYSTALLINE SILICA, AND TITANIUM DIOXIDE. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dust, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.