BEHR PREMIUM ADVANCED DECKOVER®

TEXTURED COATING

BEHR PREMIUM ADVANCED DECKOVER Textured is an innovative solid color coating that resurfaces properly prepared weathered wood and concrete. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. ADVANCED DECKOVER Textured is designed to conceal splinters & cracks up to 1/4" and creates a textured, slip-resistant finish. Our latest formula features improved dirt & fade resistance, and ease of application while maintaining film breathability. It can be tinted to 54 solid custom colors.

Recommended for properly prepared interior and exterior weathered or cracked horizontal and vertical surfaces such as:

• Wood • Composite • Concrete

Do not use on drivable surfaces such as garage floors and driveways.

TECHNICAL DATA

Tint Bases/Max Tint Load:
No. 5005 Deep Base 116 fl oz / 14 fl oz

Resin Type: 100% Acrylic

Weight per Gallon: 11.40 lb

% Solids by Volume: 47% ± 2%

% Solids by Weight: 61.3% ± 2%

VOC: < 50 g/L

Flash Point: N/A

Viscosity: 75–100 KU (Paste Paddle)

Recommended Film Thickness:
Wet: 10.7 mils / Dry: 5.0 mils per coat
(Total Dry Film Thickness: 10.0 mils for 2 coats)

Coverage: 75 sq ft/gal for 2 coats (required)

COMPLIANCE & CERTIFICATIONS

Complies with the below as of 6/1/2026

SCAQMD	YES	OTC	YES
CARB SCM 2020	YES	LADCO	YES
CARB SCM 2007	YES	EPA AIM	YES
OTC Phase II	YES	MPI®	127

Class A Fire Rating (Flame Spread Index: 0–25 & Smoke Development Index: 0–450) over non-combustible surfaces when tested in accordance with ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials.

This coating conforms to USDA regulatory requirements for incidental food-contact materials intended for use on surfaces not in direct contact with food, such as walls, ceilings, and floors.

APPLICATION

Brush: Nylon/Polyester

Roller: ¼"–½" nap roller cover, depending on surface texture

Spray: DO NOT USE WITH AIRLESS SPRAYER

- For nail holes and cracks up to ¼", completely fill in with ADVANCED DECKOVER Coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks require additional filling.
- Use pressure while rolling and apply generously.
- For optimum performance, film uniformity, leveling, adhesion and crack filling, a second coat MUST be applied. Maintain a wet edge when applying.
- For best results, coat all accessible board ends.
- For vertical surfaces such as railings, use a nylon/polyester brush or roller and apply two thin coats at a spread rate of 400 sq ft/gal.

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: 77°F & 50% RH
To Touch: 4 hours
To Recoat: 4–6 hours
Light Foot Traffic: 24–48 hours
Full Cure: 72 hours

Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION

The following steps and products are required:
(Proper surface preparation is required.)

Exterior Wood Surfaces: Replace rotting or unstable boards and remove loose splinters. For exterior failing coatings or to remove loose wood fibers, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood. When No. 64 is not needed, a product such as No. 63 MUST be used to remove mill glaze and clean the exterior wood surface. After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. Lightly sand to remove remaining wood fibers/fuzz.

Concrete Surfaces: Avoid areas that are structurally weak or subject to hydrostatic pressure above 8 psi. Allow new surfaces to cure for 30 days. Clean and etch surface using a product such as muriatic acid to achieve a textured profile similar to 150 grit sandpaper. Follow all label instructions. If the previous coating is failing or peeling, use a paint stripper to remove old coating.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

All trademarks, service marks, trade names, and trade dress appearing on this document are the property of their respective owners.

CAUTIONS/LIMITATIONS

- Protect from freezing.
- Intermix multiple containers to ensure color uniformity.
- While this textured product provides a slip resistant finish, surfaces may still become slippery when wet.
- Do not use on drivable surfaces such as garage floors and driveways.
- DO NOT USE ON wood surfaces that are in direct contact with the ground or exposed to excessive ground moisture.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Resists rain 4 hours after application. Avoid painting if humidity is expected to be greater than 80%.
- Avoid applying paint in direct sunlight or hot surfaces.
- Test product for color on a small hidden area before proceeding.
- A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.
- Shelf life under normal conditions is two years unopened.

HEALTH & SAFETY INFORMATION

WARNING! IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes. Do not breathe dusts, vapor, or spray mist. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN –
DO NOT TAKE INTERNALLY

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company Representative, call 1-800-854-0133 or visit behr.com. ©2026 Behr Process LLC, Santa Ana, CA 92705 U.S.A.