



ADVANCED DECKOVER® TEXTURED COATING

NO. 5005

PRODUCT INFORMATION

BEHR PREMIUM ADVANCED DECKOVER® Textured is an innovative, waterproofing solid color coating that will bring your old, weathered wood or concrete back to life. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. ADVANCED DECKOVER Textured is designed to conceal splinters & cracks up to 1/4" and creates a textured, slip-resistant finish. It can be tinted to 54 solid custom colors.

RECOMMENDED USES:

Recommended for properly prepared above grade interior and exterior weathered or cracked horizontal and vertical surfaces such as:

- Wood
- Composite
- Concrete

Do not use on drivable surfaces such as garage floors and driveways.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 5005 Deep Base 116 fl oz / 14 fl oz

Resin Type: 100% Acrylic

Weight per Gallon: 11.5 lbs

% Solids by Volume: 51% ± 2%

% Solids by Weight: 64% ± 2%

VOC: < 50 g/L

Flash Point: N/A

Viscosity: 87 – 115 KU (Paste Paddle)

Recommended Film Thickness:

Wet: 10.6 mils / Dry: 5.4 mils

(Total Dry Film Thickness: 10.9 mils for 2 coats)

Coverage: 75 sq ft/gal for 2 coats (required)

APPLICATION:

Brush: Nylon/Polyester

Roller: 1/4" – 1/2" nap roller cover, depending on surface texture

Spray: DO NOT USE WITH AIRLESS SPRAYER

- For nail holes and cracks up to 1/4", completely fill in with ADVANCED DECKOVER Coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks require additional filling.
- Use pressure while rolling and apply generously.
- For optimum performance, film uniformity, leveling, adhesion and crack filling, a second coat MUST be applied. Maintain a wet edge when applying.
- For best results, coat all accessible board ends.
- To create an Extra Textured finish, use Extra Textured roller cover.
- For vertical surfaces such as railings, use a nylon/polyester brush or roller and apply two thin coats at a spread rate of 400 sq ft/gal.

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: 77°F & 50% RH

To Touch: 4 hours

To Recoat: 4 – 6 hours

Light Foot Traffic: 24 – 48 hours

Full Cure: 72 hours

Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION:

The following steps and products are required:

(Proper surface preparation is required.)

Exterior Wood Surfaces: Replace rotting or unstable boards and remove loose splinters. For exterior failing coatings or to remove loose wood fibers, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood. When No. 64 is not needed, a product such as No. 63 MUST be used to remove mill glaze and clean the exterior wood surface. After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. Lightly sand to remove remaining wood fibers/fuzz.

Concrete Surfaces: Avoid areas that are structurally weak or subject to hydrostatic pressure above 8 psi. Allow new surfaces to cure for 30 days. Clean and etch surface using a product such as a muriatic acid to achieve a textured profile similar to 150 grit sandpaper. Follow all label instructions. If the previous coating is failing or peeling, use a paint stripper to remove old coating.

COMPLIES WITH THE BELOW AS OF 6/1/2020			
SCAQMD	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC Phase II	YES	MPI*	127
OTC	YES	FLAME SPREAD/CLASS A	YES

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- While this textured product provides a slip resistant finish, surfaces may still become slippery when wet.
- Do not use on drivable surfaces such as garage floors and driveways.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Do not use if rain is expected within 24 hours and avoid painting if humidity is expected to be greater than 80%.
- Avoid applying paint in direct sunlight or hot surfaces.
- Test product for color on a small hidden area before proceeding.



**ADVANCED DECKOVER® TEXTURED COATING**

NO. 5005

- A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.
- Shelf life under normal conditions is 2 years unopened.

GENERAL INFORMATION:

CAUTION! IRRITANT. HARMFUL IF SWALLOWED. CONTAINS: ACRYLIC RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY