



## ALL-IN-ONE WOOD CLEANER

### NO. 63



### PRODUCT INFORMATION

BEHR PREMIUM® All-In-One Wood Cleaner is specifically formulated to clean, brighten and condition exterior wood and composite surfaces prior to applying natural finishes, paints or stains. It's tough enough for stains caused by mold, mildew, ketchup and wine, but gentle enough that it won't damage your wood surface.

### RECOMMENDED USES:

Ideal for use on exterior substrates such as:

- Wood & Composite
- Concrete
- Vinyl Siding

### PRODUCT SPECIFICATIONS:

**Active Type:** Oxalic Acid

**Weight per Gallon:** 8.5 lb

**% Solids by Weight:** 6% ± 2%

**VOC:** <1 wt %

**Flash Point:** N/A

**Viscosity:** N/A

**Coverage:** One gallon of full strength will cover 200 sq ft/gal and diluted solution will clean and degrease up to 400 sq ft/gal and one gallon of depend on method of application, texture and surface porosity.

### APPLICATION:

**Brush:** Nylon/polyester

**Roller:** 3/8" – 3/4" nap roller cover, depending on surface texture

**Pump Sprayer:** At packaged consistency

Apply solution liberally with a pump sprayer, brush, mop or roller. Keep the surface completely wet with solution for 10-15 minutes. Scrub surface using a stiff bristle broom or brush. The solution will foam. After scrubbing, rinse thoroughly with water at normal pressure, or use a pressure washer at low setting (500-1200 PSI). Do not use high pressure.

### SURFACE PREPARATION:

Be sure to have a source for water, hose with nozzle and stiff bristle broom or brush. Wear protective clothing, goggles, acid resistant gloves. Always use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 after application of a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64. Prevent all rinse solution from entering storm drains.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

### COMPLIES WITH THE BELOW AS OF 3/1/2020

|               |     |       |     |
|---------------|-----|-------|-----|
| SCAQMD        | YES | OTC   | YES |
| CARB SCM 2007 | YES | LADCO | YES |
| OTC Phase II  | YES | AIM   | YES |

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is 2 years unopened.
- DO NOT MIX IN METAL CONTAINER.

### GENERAL INFORMATION:

**DANGER CORROSIVE** WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS: OXALIC ACID DIHYDRATE (LESS THAN 10%). MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. NOTICE: Do not mix BEHR PREMIUM NO. 63 All-In-One Wood Cleaner with chlorine bleach or with any other household or industrial cleaning product or detergent. Mix only in plastic containers. Use with adequate ventilation. Only use this product outdoors. Avoid contact with skin. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing vapor or mist. If properly used, a respirator may offer additional protection.

**FIRST AID:** Eye and skin contact: in case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY**

