



MULTI-SURFACE ROOF PAINT

NO. 65 WHITE REFLECTIVE

PRODUCT INFORMATION

BEHR® Multi-Surface Roof Paint is a premium quality, durable, 100% acrylic latex flat finish. This coating is mildew and algae resistant and will not discolor or yellow when exposed to typical high roof temperatures. It has excellent adhesion to various types of roofing materials and is tintable to match a variety of custom colors.

RECOMMENDED USES:

This product is ideal for use on properly prepared and primed above grade vertical surfaces such as:

- Concrete
- Wood
- Ferrous Metals
- Non-Ferrous Metals
- Unglazed Tile
- Masonry Shingle
- Urethane Foam
- Asphalt Shingle
- Shake Roofs
- Slate Roofs

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 65 White Reflective 126 fl oz / 4 fl oz

No. 66 Deep Base 116 fl oz / 14 fl oz

Gloss: 0 – 5 @ 60°

Sheen: 0 – 5 @ 85°

Resin Type: 100% Acrylic

Weight per Gallon: 11.5 lb

% Solids by Volume: 35% ± 2%

% Solids by Weight: 52% ± 2%

VOC: < 50 g/L

Flash Point: N/A

Viscosity: 90 – 105 KU

Recommended Film Thickness:

Wet: 6.4 mils / Dry: 2.3 mils @ 250 sq ft/gal

Wet: 3.6 mils / Dry: 1.3 mils @ 450 sq ft/gal

Coverage: 250 – 450 sq ft/gal depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller:

Smooth Surface: 3/8" – 3/4" nap

Rough Surface: 1" nap

Airless Spray:

Tip: .015" – .019"

Filter: 60 mesh

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: @ 77°F & 50% RH

To Touch: 2 hours

To Recoat: 4 hours

Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION:

- Replace brittle or cracked shingles. Clean all roof surfaces.
- Previously coated surfaces should be wire-brushed or scraped to remove all loose coating.
- Remove mildew with a mildew stain removing product.
- On galvanized metal, use a diluted solution of a cleaner and etcher to prepare surface.
- If applying on wood shakes, clean with a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63. Follow directions on product labels.
- Rinse thoroughly and allow a minimum of 24 hours to dry.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

SYSTEM RECOMMENDATIONS:

Wood & Tannin/Stain-blocking:

- 1 coat BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436
- 2 coats BEHR Multi-Surface Roof Paint

Masonry:

- 1 coat BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436
- 2 coats BEHR Multi-Surface Roof Paint

COMPLIES WITH THE BELOW AS OF 1/1/2024			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
CARB	YES	AIM	YES
OTC PHASE II	YES		

Ferrous & Non-Ferrous Metal:

- 1 coat BEHR Interior/Exterior Metal Primer No. 435 (recommended for optimal corrosion resistance or when priming over sound rusty metal surfaces) or BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436
- 2 coats BEHR Multi-Surface Roof Paint

Asphalt:

- 1 coat BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436
- 2 coats BEHR Multi-Surface Roof Paint

Previously Painted Surfaces:

- Use a full coat or spot prime with BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436 on properly prepared surfaces.

NOTE: Certain substrate and exposure conditions, as well as project requirements, may necessitate the use of other substrate-specific or solution-driven primers. Please consult with a BEHR PRO® Rep for specific primer recommendations.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.



MULTI-SURFACE ROOF PAINT

NO. 65 WHITE REFLECTIVE

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- This product is not a fire retardant.
- For best results, apply at temperatures between 50°F and 90°F. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Do not use if rain or heavy dew is expected within 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Roof surfaces may become extremely slippery when wet. Avoid walking on surface while moisture is present.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

WARNING IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes. Do not breathe dusts, vapor, or spray mist. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.