

BEHR PREMIUM® CABINET, DOOR & TRIM ENAMEL INTERIOR/EXTERIOR PAINT

- Available in Satin & Semi-Gloss Finishes
- Door Won't Stick After 2 Hours of Dry Time△
- Excellent Flow & Leveling
- Dries to a Hard, Durable Finish
- Easy Clean Surface
- Resists Dirt, Grime & Household Chemicals
- All-Weather Protection
- Sandable
- Soap & Water Clean-Up
- Mildew-Resistant Paint Finish

No. 7120 White
No. 7123 Deep Base
No. 7520 White
No. 7523 Deep Base

2 Coats Required for Optimal Durability

Spread Rate: Up to 400 sq ft Coverage

Dry Time: **1 Hr.** Dry to Touch **2 Hr.** Recoat

Clean-Up: Soap & Water

WHITE: *READY TO USE OR ADD TINTING COLORANTS.*
DEEP BASE: *DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.*
PROTECT FROM FREEZING.

WHERE TO USE

Interior or exterior wood, drywall, masonry, vinyl, aluminum, and other properly prepared and primed surfaces. Ideal for cabinets, doors, trim, molding, windows & shutters.

SURFACE PREPARATION (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains.
- Remove mildew stains with a mildew stain removing product.
- **Interior Wood Trim, Door & Cabinets:** Remove all loose and peeling paint; scuff sand glossy surfaces; caulk and repair imperfections. Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint-free cloth.
- **Exterior Wood:** Use a product such as BEHR PREMIUM No. 63 All-In-One Wood Cleaner. Thoroughly rinse the treated surfaces with clean water and allow to dry before any paint application.
- **Interior/Exterior Concrete & Masonry:** Allow new stucco, plaster and masonry to cure for 30 days. Use a concrete & masonry degreaser & cleaner to clean and prepare the surface. Powerwash to remove chalk on exterior surfaces.
- **Interior/Exterior Metal:** Etch galvanized metal.
- **Vinyl:** When applying to vinyl, color choice must be the same color or lighter than the existing color.
- For primed surfaces, sand primer coat prior to topcoating for best results.

PRIME

- Priming is recommended over all properly prepared coated or uncoated surfaces.
- For all interior surfaces, use a product such as BEHR® Kitchen, Bath & Trim Interior Stain-Blocking Primer & Sealer No. 75
- For all exterior surfaces, use a product such as BEHR Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436.
- Follow all label instructions.

APPLICATION

- DO NOT THIN.
- Stir before and during application.
- When working with more than one can of the same product, intermix to ensure color uniformity.
- Certain colors may require 2 or more coats to achieve complete hide.
- Apply when air temperature is between 50–90° F.
- Brush: Apply a thin coat using a high quality synthetic brush. For best results, apply paint with a high quality 100% Nylon brush.
- Roller: Use a high quality 1/4" nap roller cover.
- Airless Sprayer: .013"–.015" spray tip, 60 mesh filter.
- OPTIONAL: For the smoothest finish sand lightly in between coats with 320–400 grit sandpaper.
- NOTE: If touch-up is necessary, same application method is recommended.

DRY TIME

- △Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.
- Cabinets, doors and windows can be closed as early as 2 hours after final topcoat.
- After 2 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.
- Do not use on floors.

DISPOSAL

- Properly dispose of all soiled rags.
- For disposal of empty containers and unused product, contact your household refuse collection service.
- To reduce waste, consult with your retailer or an online paint calculator to determine the correct amount of paint to purchase.

LIFETIME LIMITED WARRANTY

- Visit www.behr.com/warranty or call 1-800-854-0133 for more information.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

⚠**WARNING:** This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

©2025 Behr Process LLC
Santa Ana, CA 92705 U.S.A. • behr.com
VOC < 50 g/L • REV. 11/25