



ANTI-SLIP FLOOR FINISH ADDITIVE

NO. 970

PRODUCT INFORMATION

BEHR PREMIUM® ANTI-SLIP FLOOR FINISH ADDITIVE is a texture additive designed to provide slip resistance when added to epoxy, latex paint or solid color stain for all types of interior and exterior floor surfaces. This product will not change the color of the coating when added at the recommended level.

RECOMMENDED USES:

For use with BEHR PREMIUM floor coating products, such as PORCH & PATIO FLOOR PAINT, 1-PART EPOXY, SOLID COLOR CONCRETE STAIN. Use coating on properly prepared interior or exterior surfaces including:

- Garage Floors • Patios • Stairs • Basements • Driveways
- Decks • Walkways • Pool Decks

Not for use with clear coatings, waterproofing coatings or coatings intended for application to wood surfaces.

PRODUCT SPECIFICATIONS:

Packaging: 3 oz (85 g) pouch

Composition: Polypropylene Homopolymer

MIXING INSTRUCTIONS:

FINISHED PRODUCT CONTAINER SIZE	1 QUART	1 GALLON	5 GALLONS
AMOUNT OF ADDITIVE NEEDED	1/4 pouch	1 pouch	5 pouches

Add the proper amount of BEHR® ANTI-SLIP FLOOR FINISH ADDITIVE directly to the container of any latex or oil-based floor coating finish product container and stir thoroughly until dispersed uniformly. Stir occasionally during application. Apply coating to floor surface using a brush or roller. Adding an anti-slip additive to a paint may affect application viscosity and spread rate. Refer to all paint and stain manufacturer's product labels for specific instructions on surface preparation and finish application. If applying more than one coat of floor finish, mix **ANTI-SLIP FLOOR FINISH ADDITIVE** only into the final topcoat. Adding an anti-slip additive may reduce the lifespan of the final topcoat; therefore, retain any leftover paint for periodic maintenance re-coating. Some settling may occur during storage, be sure to mix thoroughly before using.

This product, if added according to label directions, helps to prevent slipping by providing a slip-resistant coating. However, Behr does not warrant that this product will prevent accidents.

CLEAN-UP/DISPOSAL:

Refer to all paint and stain manufacturer's product labels for specific instructions on clean-up. Dispose of material in accordance with all current federal, state and local regulations. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

CAUTIONS/LIMITATIONS:

- Store in a cool, dry, well-ventilated area away from sources of heat, moisture, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
- For best results, apply coatings when air, material and surface temperatures are between 50°F and 90°F. Temperatures above 90°F can cause the coating to dry too fast. Avoid applying in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply the coating.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. CONTAINS: CARBON BLACK AND TITANIUM DIOXIDE. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF DUST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

