



## CONCRETE CRACK FILLER

NO. 972

### PRODUCT INFORMATION

BEHR PREMIUM® Concrete Crack Filler is a dry powder filler to help hide cracks found in cementitious horizontal surfaces. This product can be left uncoated or it can be used with topcoats to cosmetically improve the look of the surface.

### RECOMMENDED USES:

Ideal for use on properly prepared interior or exterior concrete and masonry surfaces including:

- Garage Floors
- Patios
- Walkways
- Driveways
- Basements
- Pool Decks

Optional BEHR PREMIUM floor coating topcoats include Porch & Patio Floor Paint, 1-Part Epoxy, Solid Color Concrete Stain and Granite Grip™. Not intended for application to wood surfaces.

### PRODUCT SPECIFICATIONS:

**Packaging:** 32 fl oz bottle

**Fill Weight:** 3.4 lbs (1.5 kg)

**Coverage (ft) by Crack Size (in):**

1/8 x 1/8 in, 307 linear ft

1/2 x 1/2 in, 19 linear ft

1/2 x 2 in, 4.8 linear ft

2 x 2 in, 1.2 linear ft

**Composition:** Silica, Portland Cement and a proprietary copolymer.

### PREPARATION:

- All cracks must be clean, sound, dry and free of any dirt or debris. Rinse cracks with a garden hose or a power washer and allow to fully dry.
- If planning to topcoat, follow surface preparation outlined on the manufacturer's label instructions.
- For best topcoat results, use NO. 880 BEHR PREMIUM Concrete Bonding Primer after BEHR PREMIUM Concrete Crack Filler has fully cured.

### APPLICATION:

- Shake bottle well, remove red cap, and cut a small opening on the spout.
- Pour into crack fully filling all voids. Do not overfill as it may be hard to remove any residual filler that cures around the surface.
- For deep cracks, an alternative filler may be used as a base layer, then top off with BEHR PREMIUM Concrete Crack Filler.
- Carefully level off and remove any excess material leaving a flush surface. Example tools to use are small brushes, putty knives, etc.
- If surface is clean, then the excess dry material can be saved and reused.

- Use a spray bottle to lightly mist with clean water and fully saturate. Avoid puddling.
- Large and deep cracks may be prone to slight shifting upon misting. A second fill and mist may be necessary to get a flush uniform finish.

### DRY TIME:

- Allow the BEHR PREMIUM Concrete Crack Filler to fully dry before applying an optional topcoat or subjecting to any traffic.
- Allow 1-hour dry time for hairline cracks up to 1/8" wide.
- Longer dry time may be required in cooler temperatures and higher humidity, and for larger cracks.

### STORAGE:

- Attach red cap back to bottle for storage.
- Store in a dry, well-ventilated area away from sources of heat, moisture, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
- Shake well before reuse.

### CLEAN-UP/DISPOSAL:

Refer to all paint and stain manufacturer's product labels for specific instructions on clean-up. Dispose of material in accordance with all current federal, state and local regulations. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

### CAUTIONS/LIMITATIONS:

- Results will vary depending on substrate color and crack size.
- Not for use to repair structural damage or for use on vertical surfaces.
- Horizontal concrete or masonry surfaces may shift due to factors such as temperature changes, heavy loads, ground settlement, and water/moisture. Periodic touch-ups may be needed to address these movements.
- For surface movement on top coated surfaces, sanding or stripping may be required before touching up with Behr Premium Crack Filler for a uniform finish. Reapply topcoat once crack filler has cured.
- Using a transparent topcoat over BEHR PREMIUM Concrete Crack Filler may cause visible darkening compared to the surface.
- Shelf life under normal conditions is two years unopened.

### GENERAL INFORMATION:

**DANGER! IRRITANT. MAY CAUSE SERIOUS INJURY TO SKIN AND EYES. MAY BE HARMFUL IF INHALED OR CAUSE IRRITATION. CONTAINS: CRYSTALLINE SILICA AND PORTLAND CEMENT.** Do not breath dusts. Wear dust mask, gloves and eye protection. Dust may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposures. Avoid sanding the material or surface upon which this product is applied. When properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection; obtain professional advice before using. If you experience irritation during application, increase fresh air or leave the area. Do not allow contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. If irritation develops or persists, get medical attention.

**KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**