



OIL-LATEX REDWOOD STAIN

NO. 9



PRODUCT INFORMATION

BEHR® Oil-Latex Redwood Stain produces a deep, redwood tone, color stain that protects exterior wood surfaces. The unique formula penetrates wood surfaces and remains flexible to resist cracking, flaking and peeling on properly prepared surfaces.

RECOMMENDED USES:

Recommended for use on exterior new or properly prepared wood surfaces such as:

- Fences
- Siding
- Planters
- Wood Patio Furniture

PRODUCT SPECIFICATIONS:

Resin Type: Oil-Latex

Weight per Gallon: 9.7 lb

% Solids by Volume: 21% ± 2%

% Solids by Weight: 33% ± 2%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 55-60 KU

Recommended Film Thickness:

Wet: 8.0 mils / Dry: 1.7 mils @ 200 sq ft/gal

Wet: 4.0 mils / Dry: 0.8 mils @ 400 sq ft/gal

Coverage: 200-400 sq ft/gal, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

For optimum performance, coat all accessible sides.

Brush: Natural Bristle

Roller: 3/8"-3/4" nap roller cover, depending on surface texture

Airless Spray:

Tip: .015"-.019"

Filter: 60 mesh

Fluid Pressure: 1,400 to 2,400 psi

Note: Follow spraying immediately with back-brushing or back-rolling for a uniform appearance.

Dry Time: @ 77°F & 50% RH

To Touch: 1 hour

To Recoat: 4 hours

Dry times are temperature, humidity and film thickness dependent.

SURFACE PREPARATION:

All surfaces must be dry, clean, free of dirt, chalk, oil, grease, wax, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

The following steps and products are recommended for best results:

If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new weathered wood, then you must use a product such as BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to clean, brighten & neutralize wood. If you do not use a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64, then use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Lightly sand any remaining wood fibers/fuzz.

WARNING Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 12/1/2019

SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
CARB	YES	AIM	YES
OTC Phase II	YES		

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Stained surfaces may become slippery when wet. Do not use on horizontal surfaces subject to foot traffic.
- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Do not apply in direct sunlight. Temperatures above 90°F can cause the stain to dry too fast, whereas temperatures below 40°F can inhibit proper film formation. Do not use if rain is expected within 24 hours.
- Test product for color on an inconspicuous area before proceeding.
- Two coats may be applied, however a more solid color appearance will result.
- Avoid applying stain too heavily. Over-application of OIL-LATEX REDWOOD STAIN results in film forming on the wood surface and therefore subject to peeling and flaking.
- Shelf life under normal conditions is 2 years unopened.

GENERAL INFORMATION:

WARNING IRRITANT HARMFUL IF SWALLOWED.

CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

