



BEHR PREMIUM® SPRAY PAINT: HIGH-SHINE

- For Indoor Projects
- Polished Finish
- Decorative Use

HIGH-SHINE GLOSS

B062644 Chrome
B063344 Gold
B065044 Copper



Protect
from Freezing



Dry to Touch: 15–30 min.
Recoat before 1 hour
or after 24 hours.



10–15 sq. ft.
Coverage



Mineral Spirits
Clean-Up

BEHR PREMIUM® High-Shine Spray Paint features an enhanced formulation that provides a unique brilliant finish for decorative projects. Designed for interior decor, BEHR PREMIUM Spray Paint is best used on smooth or sanded surfaces. The unique, ergonomic shape of the BEHR PREMIUM Spray Paint can, and its comfort tip deliver a superior spray experience that fights fatigue so you can create a smooth finish every time.

PREPARATION

The surface must be clean, free of dust, grease, wax, peeling paint, mold or mildew. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

***Peeling or Checked Paint:** Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

***Glossy Surfaces:** For maximum adhesion, scuff sand the surface thoroughly before painting.

APPLICATION

Eye protection is recommended. For best results, use at room temperature. Cover adjacent areas to protect from overspray. Shake can vigorously for one minute after mixing ball begins to rattle and often during use. Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Two to three thin coats produce best results.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process LLC warrants to the original consumer purchaser, (1) that the product meets Behr's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

DRY TIME

Longer dry time required in cooler temperatures and higher humidity. 15–30 min dry to touch. Recoat before 1 hour or after 24 hours.

CLEAN-UP & DISPOSAL

Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean. Do not stick pins or wire into can opening. Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

Visit behr.com for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. MAY CONTAIN: CYCLOHEXANE, PROPANE, HYDROTREATED LIGHT DISTILLATES, TOLUENE, ISOBUTANE, HYDRODESULFURIZED KEROSENE (PETROLEUM), ALUMINUM POWDER (STABILIZED), COPPER POWDER and HYDROTREATED HEAVY NAPHTHA DISTILLATES. May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. **KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



©2025 Behr Process LLC
Santa Ana, CA 92705 U.S.A. • behr.com
REV. 7/25