



WOOD EFFECTS WATER-BASED STAIN
NO. B4600 SERIES

PRODUCT INFORMATION

BEHR® Premium Wood Effects is a water-based stain that creates a faux aged look on all types of wood in just minutes. It is designed to mimic the color of 3 different types of aged wood such and gray, brown and black. This product provides one coat coverage and is easily applied.

RECOMMENDED USES:

Ideal for properly prepared interior, unfinished, bare wood surfaces. Not recommended for floors.

PRODUCT SPECIFICATIONS:

Premixed Colors: Available in 3 colors

- B4600 Aged Gray
- B4602 Charred Black
- B4604 Rustic Brown

Weight per Gallon: 8.3 – 8.5 lb

% Solids by Volume: 3% ± 2%

% Solids by Weight: 4% ± 2%

VOC: < 120 g/L

Flash Point: N/A

Viscosity: 15 – 40s (#2 Zahn Cup)

Recommended Film Thickness: n/a

Coverage: Up to 200 sq ft/qt depending on substrate porosity.

APPLICATION:

- Stir material thoroughly before and occasionally during use. Do not shake.
- For best results, use at temperatures between 60°F (16°C) and 90°F (32°C).
- Apply with a synthetic bristle brush or foam brush.
- Allow Wood Effects to sit on the wood for 30 minutes to 1 hour for the final effect. Wiping away is not required.
- For a lighter effect, apply product and wipe away immediately or lightly sand the finish with fine grit sandpaper once it is dry. To darken, a second coat can be applied after 1 hour.

Brush: Nylon/Polyester or foam brush

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: @ 77°F & 50% RH

To Touch: 1 hr

Topcoat: 1 hr

SURFACE PREPARATION:

All surfaces must be clean, free of dust, oil, grease, wax, polish, glue and existing coatings before staining.

- Remove any existing finishes with sandpaper or liquid stripper.
- Wood Effects works best on bare wood.
- Prepare bare wood by sanding in the direction of the grain with sandpaper.
- Remove any dust with a clean, dry rag.

CLEAR FINISH APPLICATION

- A topcoat is necessary for the best protection.
- Wait 1 hour for Wood Effects to dry before applying clear topcoat.
- For best results, use BEHR® Water-Based Fast Drying Polyurethane as a protective top coat. Test in an inconspicuous area first.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2021			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
OTC Phase II	YES	AIM	YES

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Always test stain on an inconspicuous area of the wood to verify desired color.
- Shelf life under normal conditions is two years unopened.
- Recommended finishes include BEHR® Fast-Drying Polyurethane or BEHR® Spar Urethane. Slight ambering may occur when these clear finishes are applied over light-colored stains. Always spot test on an inconspicuous area to ensure satisfactory results.

GENERAL INFORMATION:

WARNING! IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: TITANIUM DIOXIDE AND CRYSTALLINE SILICA. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experience, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

