



## BEHR PREMIUM® COLOR CHANGING MULTI-PURPOSE SPACKLING

### PRODUCT INFORMATION

Behr Premium® Color Changing Multi-Purpose Spackling is a lightweight spackling compound ideal for filling in small and large holes or cracks. This ready to use mix applies pink and dries white, allowing you to know when it is time to sand or paint. It also has excellent adhesion properties that resists sagging, shrinking, and cracking for a durable, smooth surface.

### RECOMMENDED USES:

Ideal for use on properly prepared surfaces such as:

- Drywall
- Plaster
- Wood
- Stucco

### PRODUCT SPECIFICATIONS:

**BS00217** 5.5 oz Tube

**BS00408** 16 oz Tub

**BS00404** 32 oz Tub

**Resin Type:** Acrylic

**Net Weight:** 5.5oz/135g, 16oz/400g, 32oz/800g

**% Solids by Volume:** 58% ± 3%

**% Solids by Weight:** 51% ± 3%

**VOC:** < 50 g/L

**Coverage:** Coverage varies depending on depth of repair and number of coats.

### SURFACE PREPARATION:

- The surface must be clean and dry before applying spackling compound.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION:

- Mix material gently before use.
- Spread with a putty knife and slightly overfill hole or crack.
- Allow to dry thoroughly before sanding or painting.
- Sand flush with surface.
- Repeat as necessary.
- Spackling compound will change color from pink to white when surface can accept a second application or is ready to be sanded and painted.
- Prime for topcoats of any sheen higher than flat to prevent flashing.

### CLEAN-UP/DISPOSAL:

Clean tools, equipment and excess uncured material with soap and water immediately after use. For disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS:

**To retain the effectiveness of the color changing formula, use a damp cloth to wipe access material out of the container rim, close immediately after use.**

- Store container in a cool, dry place away from extreme heat or cold. Protect from freezing.
- For best results, prime before painting with any sheen higher than flat to prevent flashing.
- Do not apply at temperatures below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use as a caulk or sealant for structural joints, cracks, floors, or exterior substrates where expansion and contraction may occur.
- For exterior use, seal and topcoat with an exterior system.
- Wash hands thoroughly after handling.
- Shelf life of unopened container is 12 months from date of manufacture when stored under normal conditions.

### GENERAL INFORMATION:

**WARNING! IRRITANT.** CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: TITANIUM DIOXIDE, CALCIUM CARBONATE AND CRYSTALLINE SILICA. Avoid contact with skin and eyes. Do not breathe dusts, vapor, or spray mist. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN.**

