

**PRO****HIGH BUILD INTERIOR PRIMER****NO. PR040****PRODUCT INFORMATION**

BEHR PRO™ High Build Interior Primer is recommended for new and previously coated drywall and plasterboard walls and ceilings. Spray application can save time by combining the skim coat operation with the prime application. It helps hide minor surface defects, minimizes joint banding & photographing and equalizes the porosity of the surface.

RECOMMENDED USES:

Ideal for use on commercial and residential properties. When properly applied to a drywall surface with a minimum of a Level 4 finish, **BEHR PRO High Build Interior Primer** will provide a Level 5 finish. This is particularly important for critical lighting situations: long hallways, large wall areas, and high sheen finishes. May also be used where rough and/or uneven surfaces prevent uniform coverage and application of the topcoat.

- Drywall
- Plaster

PRODUCT SPECIFICATIONS:**Resin Type:** PVA**Weight per Gallon:** 12.6 lb**% Solids by Volume:** 41% ± 2%**% Solids by Weight:** 61% ± 2%**VOC:** < 100 g/L**Flash Point:** N/A**Viscosity:** 120 – 130 KU**Recommended Film Thickness:**

Wet: 21.3 mils / Dry: 8.8 mils @ 75 sq ft/gal

Wet: 16.0 mils / Dry: 6.6 mils @ 100 sq ft/gal

Coverage: 75 – 100 sq ft/gal, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:**Brush:** Not recommended**Roller:** Not recommended**Airless Spray:****GPM:** Minimum 1.0 GPM output sprayer**Tip:** .019" – .021"**Filter:** Remove**Fluid Pressure:** 1,400 – 2,400 psi

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: 77°F & 50% RH**To Touch:** 1 hours**To Recoat:** 4 – 8 hours

Dry times are temperature, humidity and film thickness dependent.

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

Drywall: All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating.

Plaster: New plaster should be thoroughly dry and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 6/1/2020

SCAQMD	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC Phase II	YES	LEED v.3 (2009) [†]	YES
OTC	YES		

This coating conforms to the United States Department of Agriculture (USDA) regulatory requirements for incidental food-contact materials intended for use on surfaces not in direct contact with food, such as walls, floors and ceilings.

[†]Please visit www.usgbc.org/LEED for additional details.

CAUTIONS/LIMITATIONS:

- Interior use only.
- Do not use on floors.
- Do not use over previously painted surfaces.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

CAUTION IRRITANT MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

