



BLOCK FILLER PRIMER

NO. PR050

PRODUCT INFORMATION

BEHR PRO® Block Filler Primer is an economical interior / exterior latex primer formulated to fill and seal porous masonry surfaces, reduce pinholing and help produce a smooth and even topcoat for a uniform, professional quality finish.

RECOMMENDED USES:

Use on properly prepared, above-grade interior or exterior surfaces, such as:

- Concrete
- Cement Board Siding
- Concrete Block/CMU
- Stucco
- Brick
- Plaster

PRODUCT SPECIFICATIONS:

Resin Type: Acrylic Copolymer

Weight per Gallon: 13.5 lb

% Solids by Volume: 50% ±2%

% Solids by Weight: 69% ±2%

VOC: < 100 g/L

Flash Point: N/A

Viscosity: 100 – 105 KU

Recommended Film Thickness:

Wet: 21.4 mils / Dry: 10.7 mils @ 75 sq ft/gal

Wet: 10.7 mils / Dry: 5.3 mils @ 150 sq ft/gal

Coverage: 75 – 150 sq ft/gal depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/4" – 1 1/2" nap roller cover, depending on surface texture

Airless Spray:

Tip: .019" – .025"

Filter: Remove

Fluid pressure: 2,000 – 3,200 psi

Thinning: DO NOT THIN. Product is formulated for use at package consistency only.

Dry Time: @ 77°F & 50% RH:

To Touch: 1 hour

To Recoat: 2 hours

Dry times are temperature, humidity and film thickness dependent.

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

- If washing is necessary, use a non-soapy detergent or TSP substitute. Rinse well and allow to dry.
- This product is only designed to be used on unpainted masonry surfaces that have been allowed to cure at least 30 days with a moisture content below 15% before application.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

PERFORMANCE DATA:

Wind Driven Rain Resistance (ASTM D6904/TT-C 555B):

Result: Pass

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 6/1/2020

SCAQMD	YES	GREENGUARD®	YES
CARB SCM 2007	YES	LEED V.4 [†]	YES
OTC Phase II	YES	MPI	4
OTC	YES	MPI X-GREEN	4
AIM	YES		

This coating conforms to the United States Department of Agriculture (USDA) regulatory requirements for incidental food-contact materials intended for use on surfaces not indirect contact with food, such as walls, floors and ceilings.

[†]GREENGUARD is a registered trademark of UL Company.

[†]Please visit www.usgbc.org/LEED for additional details.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Do not apply in direct sunlight. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Do not apply to shiny or slick surfaces or loss of adhesion may occur. These surfaces can be prepared with chemical etchers and/or sandblasting.
- Shelf life under normal conditions is 2 years unopened.



**BLOCK FILLER PRIMER**

NO. PR050

GENERAL INFORMATION:

CAUTION IRRITANT MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

