



e600 EXTERIOR SEMI-GLOSS PAINT

NO. 670 WHITE BASE



PRODUCT INFORMATION

BEHR PRO™ e600 Exterior Semi-Gloss Paint is specifically designed to meet the demanding expectations of professional painters. Developed for optimal sprayability, this 100% acrylic formula provides excellent hiding power and a highly uniform, mildew resistant finish. BEHR PRO Semi-Gloss Paint is a durable, washable finish for exterior walls and trim. Not for use on floors.

RECOMMENDED USES:

Ideal for both commercial and residential properties over properly prepared:

- Concrete, Concrete Tilt-Up
- Concrete Block/CMU
- Cement Board Siding
- Brick
- Stucco
- Wood
- Plywood
- Ferrous Metals
- Non-Ferrous Metals
- Vinyl Siding

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. 670 124 oz. / 6 oz.
- No. 674 117 oz. / 13 oz.
- No. 673 116 oz. / 14 oz.

Gloss: 45-55 @ 60°

Resin Type: 100% Acrylic

Weight per Gallon: 10.19 lbs.

% Solids by Volume: 32%

% Solids by Weight: 44%

VOC: <50 g/L

Flash Point: N/A

Viscosity: 95-105 KU

Recommended Film Thickness:

- Wet: 6.4 mils; Dry: 2.0 mils @ 250 Sq. Ft./Gal.
- Wet: 4.0 mils; Dry: 1.3 mils @ 400 Sq. Ft./Gal.

Coverage: 250-400 Sq. Ft./Gal., depending on the surface texture, porosity and application method. Does not include the loss of material from spraying. Film thickness depends on porosity and various substrate irregularities.

APPLICATION:

Brush: Nylon/polyester

Roller:

- Smooth Surfaces: 3/8"-1/2" nap
- Porous Surfaces: 1/2"-3/4" nap

Airless Spray: Fluid pressure of 1,500 - 2,200 psi

Tip: .015" - .021"

Filter: 60 mesh

Thinning: Not recommended. Product is formulated for use at package consistency only.

Dry Time: 77°F (25°C), 50% RH:

Longer dry time may be required in cooler temperatures and higher humidity.

To Touch: 2 hours

To Recoat: 4 hours

Full Cure: 14 days

SURFACE PREPARATION:

- All surfaces must be clean, free of dust, chalk, oil, grease, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.
- Glossy surfaces must be 'scuff sanded' with an appropriate sandpaper and primed prior to coating.
- Allow new stucco, plaster and masonry to cure for 30 days before painting.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS:

PROPERLY PREPARED NEW SURFACES:

Wood: Composition Panels/Siding, Fiber Board

- BEHR PREMIUM PLUS® Interior/Exterior Multi-Surface Primer & Sealer No. 436

Wood: Cedar, Redwood, Shakes & Shingles

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

Tannin/Stainblocking:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

COMPLIES WITH THE BELOW AS OF 3/1/16

SCAQMD	YES	AIM	YES
CARB	YES	LEED v.3 (2009)†	YES
OTC	YES	MPI#	11
LADCO	YES		

†Please visit www.usgbc.org/LEED for additional details.

Masonry: Stucco, Cinder Block, Concrete Masonry Units (CMUs), Split Face Block

- BEHR PREMIUM® Interior/Exterior Basement & Masonry Waterproof No. 875 (can also be used as a block filler.)
- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco

- BEHR PREMIUM Interior/Exterior Basement & Masonry Waterproof No. 875 (can also be used as a block filler.)
- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

Masonry with pH Levels up to 13.0:

- BEHR PREMIUM Interior/Exterior Basement & Masonry Waterproof No. 875
- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

Ferrous & Non-Ferrous Metals:

- BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

PREVIOUSLY PAINTED SURFACES:

- Use a full coat or spot prime with BEHR PREMIUM PLUS Interior/Exterior Multi-Surface Primer & Sealer No. 436

CLEAN UP:

- Clean all tools and equipment with clean water.
- For proper disposal of empty containers and unused product, contact your local household refuse collection service.
- To reduce waste, consult with your retailer or an online paint calculator to determine the correct amount of paint to purchase.



e600 EXTERIOR SEMI-GLOSS PAINT

NO. 670 WHITE BASE

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- IMPORTANT! Do not open can without reading instructions.
- For tint bases-do not use without the addition of colorant.
- Do not use on glossy surfaces or floors.
- Do not use when air and surface temperatures are below 35°F or above 90°F.
- Allow 2 weeks for full cure before washing or cleaning.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.