

CRAFTER™ +
COLORBODY™ & GLAZED PORCELAIN FLOOR
WITH STEPWISE™ TECHNOLOGY



50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

AMERICAN OLEAN®



CONCRETE LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

CRAFTER™

Transform any space to reflect your artistic vision with Crafter™, a concrete look inspired by visuals of unique fibers found in craft paper. Popular large-format sizes available in five on-trend colors offer a clean canvas to achieve various design aspirations; two 8" hex decos create an eye-catching 3D effect with a strong aesthetic appeal. Reach new heights of contemporary design in both commercial and residential spaces.



STEPWISE™

**50% MORE
SLIP RESISTANT
THAN ORDINARY TILE***

*When compared to tile meeting ANSI Standards.

AMERICAN CLEAN



PROVEN IN TILE

Cover photo features Paper Block 8 x 8 Hex on the floor.
Above photo features Sketch 24 x 24 on the floor and Waterwood™ White Oak 8 x 40 on the wall.

CRAFTER™ +

COLORBODY™ & GLAZED PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

50% MORE SLIP RESISTANT THAN ORDINARY TILE*



AMERICAN OLEAN®



FINISHES: MATTE

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
FLOOR WALL COUNTERTOP SHOWER FLOOR EXTERIOR FLOOR	PC COLORBODY PORCELAIN PG GLAZED PORCELAIN	LOW HIGH	STEPWISE™ TRUEDGE™ REVEAL SYNC3D™ MADE IN THE U.S.A. LARGE FORMAT MOSAIC/DECO ENCAUSTIC TERRAZZO PAVER CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

CONCRETE LOOK

COLORBODY™ PORCELAIN FLOOR TILE



PAPIER-MACHE CF15



TWILL CF16



ORIGAMI CF17



SKETCH CF18



INK CF19

GLAZED PORCELAIN 8" HEXAGON FLOOR TILE



PAPER BLOC CF20



CARBON BLOC CF21

--	--	--	--	--	--	--	--

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE


USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	FINISH	MADE IN U.S.A
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M	
	12 x 24 Floor Tile*	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M	
	8" Hexagon Floor Tile	7-7/8" x 9-1/16" (19.95 cm x 23.04 cm)	5/16"	M	

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information.

M Matte Finish

*StepWise™ Technology available in the 12 x 24 floor tile only.

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors - Standard Center Drain	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	●*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	●
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* 12 x 24 floor tile only.

FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

CONCRETE LOOK

TRIM

			NUMBER	FINISH
	Bullnose	3 x 24	P43F9	M
	Cove Base	6 x 12	P36C9TB	M
	Cove Base Corner	1 x 6	PC36C9TB	M

M Matte Finish

INSTALLATION & PRICING

Grout Joint Recommendation	Shade Variation
<p>24 x 24 and 12 x 24 Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p>8" Hex: 3/16"</p>	<p>MEDIUM (V2)</p>

PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.