

CROSSWOOD™
GLASS

AMERICAN OLEAN®



MOSAIC



AMERICAN OLEAN®
PROVEN IN TILE™

CROSSWOOD™

Perfect for accent walls and backsplashes in kitchens or bathrooms, Crosswood™ is an eye-catching mix of shimmering earth tones. Available in two neutral color palettes this hexagonal glass mosaic tile creates stunning designs that offer unlimited design possibilities.



Cover and above photos feature Pelican Hexagon Mosaic on the wall.

FINISHES: GLOSSY


USAGE



MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MOSAIC

HEXAGONAL GLASS MOSAIC



SEAGULL CR95



PELICAN CR96



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: GLOSSY


USAGE



MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MOSAIC

SIZES

	THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
 1-1/2" Hexagonal Glass Mosaic (Mesh-mounted) 11" x 11-13/16" Sheet (27.94 cm x 30.00 cm Sheet)	1/4"	12.18	14

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	●
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	●

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

FEATURES



REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Mosaic: 1/8"	 RANDOM (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 250 lbs.
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.

