

IMPRESA™

GLAZED CERAMIC FLOOR, WALL & MOSAIC WITH REVEAL IMAGING®

MARBLE LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

IMPRESA™

With the look of Brescia marble, Impresa is destined to be a timeless selection. Detailed graphics reveal a soft linear marble look that is modern in design and classic in style. A unique size offering with neutral colors makes this series adaptable to a wide range of color schemes and design opportunities.



Cover photo features Impresa Charcoal 12 x 24 on the floor and Light Gray 4 x 12 on the backsplash.

Above photo features Impresa Light Gray 12 x 24 on the floor, 4 x 12 on the tub sides and bottom part of wall with 2 x 2 mosaic on the top part of the wall.

IMPRESA™

GLAZED CERAMIC FLOOR, WALL & MOSAIC WITH REVEAL IMAGING®

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

GLAZED CERAMIC FLOOR TILE



LIGHT GRAY IM08



TAUPE IM09

GLAZED CERAMIC WALL TILE



LIGHT GRAY IM08



TAUPE IM09

GLAZED CERAMIC MOSAIC



LIGHT GRAY IM08



TAUPE IM09

JOLLY TRIM



LIGHT GRAY IM08



TAUPE IM09



VISIT AMERICANLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

IMPRESA™

GLAZED CERAMIC FLOOR, WALL & MOSAIC WITH REVEAL IMAGING®

FINISHES: MATTE

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
FLOOR WALL COUNTERTOP SHOWER FLOOR EXTERIOR FLOOR			STEPWISE™ TRUEEDGE™ MADE IN THE U.S.A. LARGE FORMAT MOSAIC/ DECO ENCAUSTIC TERRAZZO PAVER CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	11-9/16" x 23-3/8" (29.40 cm x 59.30 cm)	3/8"	15.04	8
	4 x 12 Wall Tile	4-1/4" x 12-7/8" (10.91 cm x 32.77 cm)	5/16"	10.64	28
	13 x 13 Floor Tile	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●**
Shower Floors (Residential or Light Commercial)	≥ 0.42	●**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Wall tile not suitable for this application.

** Mosaic tile only

FEATURES

	POST-CONSUMER RECYCLED MATERIALS		PRE-CONSUMER RECYCLED MATERIALS
	MADE IN THE U.S.A.		REVEAL IMAGING®



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P43C9	30
	Jolly	1/2 x 12	S1/212J	6 CARDS*

*4 Pieces per card

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p>Wall: 1/16" (When rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p>Mosaic: 1/8"</p>	<p>MEDIUM (V2)</p>

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs.	120 - 230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	7.0	4.0 - 6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

888.AOT.TILE



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

©2022 AMERICAN OLEAN (02/22)



LEARN MORE